Product data sheet Characteristics

NSYS3DC10825

WM S3DC plain door w/o plain chassis, w/o cable gland plate. H1000xW800xD250mm.



Main	
Range	Spacial
Product name	Spacial S3DC
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	39.37 in (1000 mm)
Enclosure nominal width	31.50 in (800 mm)
Enclosure nominal depth	9.84 in (250 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock

Complementary

Body type	Gutter-shaped front profile double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, screw driver insert	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Steel	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product certifications	UL	
Net weight	71.87 lb(US) (32.6 kg)	

Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262

Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL	
Discount Schedule	ES1	
GTIN	00785901662815	
Nbr. of units in pkg.	1	
Package weight(Lbs)	75.9 lb(US) (34.43 kg)	
Returnability	Yes	
Country of origin	ES	

Packing Units

Package 1 Height	43.31 in (1100.000 mm)
Package 1 width	32.48 in (825.000 mm)
Package 1 Length	12.01 in (305.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	[™] REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months	
vvairanty	To months	