# Product datasheet Characteristics

## NSYSBM404012

Metal industrial box plain door H400xW400xD120 IP66 IK10 RAL 7035



#### Main

· · · · · · · · · · · · · · · · · · ·		
Range	Spacial	
Product name	Spacial SBM	
Device application	Multi-purpose	
Product or component type	Industrial box	
Device short name	SBM	
Enclosure type	Flat face box	
Enclosure nominal height	400 mm	
Enclosure nominal width	400 mm	
Enclosure nominal depth	120 mm	
Enclosure mounting	Wall mounted	
Device composition	1 x body	
	1 x cover	
	4 x cover screw	
Body type	Single piece body folded and welded	
Type of front cover	Plain door	
Cover fixing	Half turn metal screw	
Lock type	Outside sealed area: PZ2 screwdriver captive screw	
Removable parts	Cover, by captive screws	

#### Complementary

	<u></u>
Sheet steel	ple
Polyester powder	i de
Grey ( RAL 7035 )	<u> </u>
IEC 62208	in i
LR GL DNV UL BV	claimer. This docur
	Polyester powder  Grey ( RAL 7035 )  IEC 62208  LR GL DNV UL

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for storage	-3560 °C
Ambient air temperature for operation	-3580 °C

### Offer Sustainability

Green Premium product
Compliant - since 1241 - Schneider Electric declaration of conformity
Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
Reference not containing SVHC above the threshold
Available
Need no specific recycling operations

#### Contractual warranty

o o management	
Warranty period	18 months