# Product datasheet Characteristics

# NSYTBS191610HT

ABS box IP66 IK07 RAL7035 Int.H175W150D100 Ext.H193W164D105 Transp.cover H40



#### Main

Range	Thalassa	
Product name	Thalassa TBS	s bilbon
Device application	Multi-purpose	
Product or component type	Industrial box	of these
Height	192 mm	
Width	164 mm	reliability Villiability
Depth	105 mm	
Internal height	175 mm	en in a contraction of the contr
Internal width	150 mm	
Internal depth	100 mm	emericina.
Enclosure mounting	Wall mounted	<u> </u>
Device composition	1 x body 1 x cover 4 x cover screw	d bringed for
Body type	One piece moulded	
Type of front cover	High transparent cover	
Cover fixing	Plastic screws	Ţ
Lock type	Outside sealed area: flat screwdriver captive screw	cu hastirite
Removable parts	Cover, by captive screws	

#### Complementary

Material	ABS	not
Colour	Grey ( RAL 7035 ) Transparent	ntation is
Standards	IEC 62208	
Product certifications	DEMKO SEMKO TÜV	ner: This do
IP degree of protection	IP66conforming to NEMA 4.4X	isolair

IK degree of protection	IK07conforming to IEC 62262
Fire resistance	650 °C conforming to IEC 60695-2-11
Ambient air temperature for storage	-1540 °C
Ambient air temperature for operation	-2560 °C

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months