



Family

Catalog Number: NVNZ-M253S-11
Product ID: 7TAA292150R0726
UPC Number: 78620996463
EAN Number: 07630030254840
Status: Active

VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68 - Thread M25x1.5, Conduit Size NW 23, Thread Length 11, with Sealing Insert, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121719 Strain reliefs
IGCC	5067 Strain reliefs
Brand Name	PMA
Type	Fittings for Nylon Flexible Conduits
Application	Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas
Trade Size	NW23
Hub Size	M25x1.5
Bend	Straight
Material	Polyamide 6 with Nickel Plated Brass Threads
Color	Black

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	25mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M25 x 1.5
Thread material	Brass
Thread length	11mm
Total length	78.5mm
Material	Polyamide
Material sealing	Other
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	30
Outer Quantity	120
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.13 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

Header

3D Model

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com