



Email

Products Industries About TE Resources My Account Innovation Support Center

🕒 Add to My Part List 🛛 📆 Request Sample 🍈 Find Similar Products 🛮 🚭 Buy Product

Home > Products > Relays > Product Feature Selector > Product Details

OMIH-SH-124D,394 Product Details



OMIH-SH-124D,394

(1461373-9) TE Internal Number: 1461373-9

Active

🔁 View 3D PDF

Industrial Relays (General Purpose)

Always EU RoHS compliant but not ELV Compliant (Statement of Compliance)

Product Highlights:

- OMI/OMIH Series
- · Contact Current Class = 10A to 20A Class, Greater Than 16A
- Contact Rated Current = 16 A
- Terminal Type = PCB-THT
- Contact Arrangement = 1 Form C (CO)

View all Features





Share

What can we help you find?

- Pricing & Availability
- Search for Tooling
- Product Feature Selector Contact Us About This Product

Print

Documentation & Additional Information

Product Drawings:

OMIH CUSTOMER DRAWING (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version C2)
- 3D Model (IGES, Version C2)
- 3D Model (STEP, Version C2)

Additional Information:

Product Line Information

Additional Product Images:

- Schematic
- Wiring Diagram
- PCB Layout (Bottom Surface)

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Series = OMI/OMIH
- Terminal Type = PCB-THT

Electrical Characteristics:

- . Contact Current Class = 10A to 20A Class, Greater Than 16A
- Contact Rated Current (A) = 16 Contact - Limiting Continuous Current (A) = 16
- Contact Limiting Making Current (A) = 16
- Contact Limiting Breaking Current (A) = 16
- Insulation Initial Dielectric Between Coil/Contact Class = >4000V Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000
- Insulation Initial Dielectric Between Contacts and Coil (V rms) =
- Contact Rated Voltage (VAC) = 250
- Contact Switching Voltage Max. (VAC) = 250 Contact - Switching Voltage Max. (VDC) = 30
- Contact Limiting Short-Time Current (A) = 16
- Contact Switching Recommended Load, Min. = 100mA at 5V
- Coil Rated Voltage (VDC) = 24
- Coil Resistance (Ω) = 820
- Coil Rated Power, DC (mW) = 720
- Coil Rated Power Class = 600mW to 800mW Class
- Insulation Initial Insulation Resistance (MΩ) = 1000000
- Insulation Creepage Class = 5.5mm to 8mm Class
- Insulation Clearance Class = 5mm to 8mm Class
- Insulation Special Features = 10000V Initial Surge Withstand Voltage between Contacts and Coil

Dimensions:

- Mechanical Length Class = 25mm to 30mm Class
- Length (mm [in]) = 29.21 [1.150]
- Mechanical Width Class = 12mm to 16mm Class Width (mm [in]) = 12.80 [0.504]
- Mechanical Height Class = 20mm to 25mm Class
- Height (mm [in]) = 20.60 [0.811]
- Insulation Clearance Between Contact and Coil (mm [in]) = 5.5 [0.217]
- Insulation Creepage Between Contact and Coil (mm [in]) = 8 [0.315]

Body Features:

- Mount Type = PCB
- Weight (g [oz]) = 13.00 [0.459]

Contact Features: Contact Material = AgSnO

- Contact Number of Poles = 1

Configuration Features:

- Contact Arrangement = 1 Form C (CO)
- Coil Magnetic System = Monostable, DC
- Coil Special Features = UL Coil Insulation Class A

Industry Standards:

- RoHS/ELV Compliance = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS not ELV compliant
- Approved/Registered Standards = CQC, UL, CSA, VDE

Environmental:

- Environmental Category of Protection = RTIII
- Environmental Ambient Temperature, Max. (°C [°F]) = 60 [140]
- Environmental Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:

Packaging Method = Box

Other:

Brand = OEG

Corporate Information

About TE Investors News Room Supplier Portal

Careers Terms & Conditions

Privacy Policy

Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings

Product Compliance Support Center

Email or Chat With Us Find a Phone Number

Customer Support

Knowledge Base Manage Your Account

Keep Me Informed

Receive TE News, Events & Technology Updates







Site Map