



CIRCUIT: DPST (NORMALLY OPEN)

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. RATING: AC 250V 5A; IN-RUSH: 80A, TV-5
4. CONTACT RESISTANCE: 50m ohms MAX. (AT DC 5V 1A)
5. DIELECTRIC STRENGTH: AC 1,000V FOR 1 MINUTE
6. OPERATING FORCE: 500±100gf
7. TRAVEL: Full: 4.0mm; Lock: 2.5mm
8. 2002/95/EC (RoHS) COMPLIANT

C	16233	BUTTON PN WAS A0411601	7/14/06	RC
B	13992	CORRECT THE CIRCUIT DIAGRAM	5/6/04	AR
A	11962	RELEASED FOR PRODUCTION	2/11/02	CB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE		DR		DWG		REV	
P297 EE PB (TAG/BLK)		1.5:1		6/7/99		MM		XP02384		C	



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED