

A.
System
Overview

Adhesive Tape for Wiring Duct

B1.
Cable Ties

- Recommended installation temperature is 70°F (21°C)
- Optimum recommended dwell time for acrylic adhesive is 8 hours
- UL Recognized service temperature is 32°F (0°C) to 140°F (60°C)
- Recommended tape load is 1/2 lb. per square inch of tape area

B2.
Cable
Accessories



B3.
Stainless
Steel Ties

| Duct Size (W x H) | Tape Part Number | Roll Length | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|----------------------|------------------------|----------------|------|----------------------|----------------------|
| | | Yds. | m | | |
| .5 x .5 thru 1.5 x 4 | P32W2A2-50-7 | 7.0 | 6.4 | 1 | 100 |
| | P32W2A2-50-72 | 72.0 | 65.5 | 1 | 9 |
| 2 x 1 thru 3 x 3 | P32W2A2-50-7 | 7.0 | 6.4 | 1 | 100 |
| | P32W2A2-50-72 | 72.0 | 65.5 | 1 | 9 |
| 3 x 4 thru 3 x 5 | P32W2A2-75-7 | 7.0 | 6.4 | 1 | 60 |
| | P32W2A2-75-72 | 72.0 | 65.5 | 1 | 7 |
| 4 x 1.5 thru 4 x 3 | P32W2A2-50-7 | 7.0 | 6.4 | 1 | 100 |
| | P32W2A2-75-72 | 72.0 | 65.5 | 1 | 9 |
| 4 x 4 thru 6 x 4 | P32W2A2-75-7 | 7.0 | 6.4 | 1 | 60 |
| | P32W2A2-75-72 | 72.0 | 65.5 | 1 | 7 |

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

Specifications for Factory Applied Tape

C4.
Cable
Management

| Duct Size (W x H) | Rows of Tape | Tape | | | |
|-------------------------|-----------------|-------|------|-----------|----|
| | | Width | | Thickness | |
| | | In. | mm | In. | mm |
| .5 x .5 through .75 x 2 | 1 | .50 | 12.7 | .03 | .8 |
| 1 x 1 through 1.5 x 4 | 1 | .75 | 19.1 | .03 | .8 |
| 2 x 1 through 3 x 3 | 2 | .50 | 12.7 | .03 | .8 |
| 3 x 4 through 3 x 5 | 2 | .75 | 19.1 | .03 | .8 |
| 4 x 1.5 through 4 x 3 | 2 | .50 | 12.7 | .03 | .8 |
| 4 x 4 through 6 x 4 | 2 | .75 | 19.1 | .03 | .8 |

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index