

Adhesive Tape

- Recommended installation temperature is 70°F (21°C)
- UL Recognized service temperature is 32°F (0°C) to 140°F (60°C)
- Optimum recommended dwell time for acrylic adhesive is 8 hours
- Recommended tape load is 1/2 lb. per square inch of tape area



Duct Size (W x H)	Tape Part Number	Roll Length		Std. Pkg. Qty.	Std. Ctn. Qty.
		Yds.	m		
0.5 x 0.5 – 1.5 x 4	P32W2A2-50-7	7	6.4	1	100
	P32W2A2-50-72	72	65.5	1	9
2 x 1 – 3 x 3	P32W2A2-50-7	7	6.4	1	100
	P32W2A2-50-72	72	65.5	1	9
3 x 4 – 3 x 5	P32W2A2-75-7	7	6.4	1	60
	P32W2A2-75-72	72	65.5	1	7
4 x 1.5 – 4 x 3	P32W2A2-50-7	7	6.4	1	100
	P32W2A2-75-72	72	65.5	1	9
4 x 4 – 6 x 4	P32W2A2-75-7	7	6.4	1	60
	P32W2A2-75-72	72	65.5	1	7

Specifications For Tape Application

Duct Size (W x H)	Rows of Tape	Tape			
		Width		Thickness	
		In.	mm	In.	mm
0.5 x 0.5 – 0.75 x 2	1	0.50	12.7	0.03	0.8
1 x 1 – 1.5 x 4	1	0.75	19.1	0.03	0.8
2 x 1 – 3 x 3	2	0.50	12.7	0.03	0.8
3 x 4 – 3 x 5	2	0.75	19.1	0.03	0.8
4 x 1.5 – 4 x 3	2	0.50	12.7	0.03	0.8
4 x 4 – 6 x 4	2	0.75	19.1	0.03	0.8