


Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFP18-6RHT6C
 - Part Drawings
 - PDFRing Termina..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'P8-10RHT6-Q'

Your search criteria matched only one product, shown below

P8-10RHT6-Q



- Nickel plated copper for temperatures up to 650°F (343°C)
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process
- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Rated up to 2000 V

| | |
|-------------------------------|---|
| Part Number | P8-10RHT6Q |
| RoHS Compliancy Status | Compliant |
| Part Description | High Temperature Ring Terminal, 8 AWG, #10 stud size, noinsulated. |
| Product Type | Terminals |
| CSA Certified | Pending |
| UL Listed | Yes |
| Length (In.) | 1.14 |
| Length (mm) | 29.0 |
| Width (In.) | 0.42 |
| Width (mm) | 10.7 |
| CE Compliant | No |
| Clearance | 0.43 |
| Clearance (mm) | 10.9 |
| Insulation | Non-Insulated |
| Panduit Color Code | No Color NonInsulated |
| Plating Type | Nickel |
| Pricing Description | Ring Terminal, high temperature, norinsulated, 8 awg, #10 stud size |
| Stock | 0.04 |
| Stock (mm) | 1.0 |
| Stud Size | #10 |
| Temperature Rating | 650 Degrees Fahrenheit (343 Degrees Celsius) |
| Tool | CT-2600, CD-2600-8† |
| Wire Range | 8 AWG |
| Wire Range (mm ²) | 10 |
| Min. Order UOM | PC |
| Min. Order Qty. | 25 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List |  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.