


Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDF Ring Termina..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'P8-8RN-T'

Your search criteria matched only one product, shown below

P8-8RN-T



- Designed for use with #8 – 2 AWG copper wire
 - Ring tongue design assures a secure connection in high vibration applications
 - Internal barrel serrations assure good wire contact and maximum tensile strength
 - Brazed seam protects terminal barrel from splitting during the crimp process
 - Barrel of terminal internally beveled to provide quick and easy wire insertion
 - Maximum recommended operating temperature 302°F (150°C)
 - UL and CSA rated up to 2000 V per UL 486A/B, where applicable
- ‡UL and CSA approved tooling/product combinations.

Part Number	P8-8RNT
RoHS Compliancy Status	Compliant
Part Description	Ring terminal, large wire, narrow tongue, 8 AWG, #8 stud size, non-insulated.
Product Type	Terminals
CSA Certified	No
UL Listed	No
Length (In.)	1.09
Length (mm)	27.7
Width (In.)	0.36
Width (mm)	9.1
CE Compliant	No
Clearance	0.43
Clearance (mm)	10.9
Insulation	Non-Insulated
Panduit Color Code	No Color NonInsulated
Plating Type	Tinned
Pricing Description	Ring Terminal, large wire, narrow tongue, non-insulated, 8 AWG, #8 stud size
Stock	0.04
Stock (mm)	1.0
Stud Size	#8
Temperature Rating	302 Degrees Fahrenheit (150 Degrees Celsius)
Tool	CT-1701, CT-2600 With Die Insert CB2600-8‡
Wire Range	8 AWG
Wire Range (mm ²)	10.0
Min. Order UOM	PC
Min. Order Qty.	200
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.