TE connectivity

🛒 My Cart | 📑 My Part Lists | Sign In/Register   🌐 English (Change)

What can we help you find?   🔍

Have a Question?
Chat with a Product
Information Specialist

Products **Industries** **Resources** **About TE** **Support Center** **My Account**

Home > Products > Filters > Product Feature Selector > Product Details

# 7-6609928-3 Product Details

➕ Share   🖨 Print   ✉ Email

EMI/RFI Filters and Accessories

🍃 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:
- Filter - EMI/RFI
- Filter Type = Power Entry (Filtered/Unfiltered)
- P (3-10 Amp) Series
- General Purpose Application
- Mount Style = Flanged

View all Features

7-6609928-3
(PE0SSDSXA)
TE Internal Number: 7-6609928-3
✔ Active

🔴 View 3D PDF

📥 Add to My Part List   📦 Request Sample   🌐 Find Similar Products   🪙 Buy Product

Quick Links
▸ Check Pricing & Availability
▸ Search for Tooling
▸ Product Feature Selector
▸ Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- Customer Drawing P-Series (PDF, English)

Catalog Pages/Data Sheets:
- 1-1654250-1_CORCOM_EMI_RFI_QRG (PDF, English)

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files: (CAD Format & Compression Information)
- 2D Drawing (DXF, Version A)
- 3D Model (IGES, Version A)
- 3D Model (STEP, Version A)

Additional Information:
- Product Line Information

Additional Product Images:
- Insertion Loss/Specifications

Related Products:
- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type = Filter - EMI/RFI
- Filter Type = Power Entry (Filtered/Unfiltered)
- Series = P (3-10 Amp)
- Filtered = Yes
- Type of Connector = IEC 320/C-14

Mechanical Attachment:
- Shield Style = Filter Shield

Electrical Characteristics:
- Input Voltage Select = Dual AC Voltage (SMPS)
- Current Rating (A) = 10
- Voltage Selection = 2 Voltage
- Voltage ≤ (VAC) = 250
- Leakage Current (Line-to-Ground) Max. @ 250 VAC 50 Hz (mA) = 0.5
- Leakage Current (Line-to-Ground) Max. @ 120 VAC 60 Hz (mA) = 0.25

Termination Features:
- Terminal Input - Output Combination = IEC - .187" Faston

Body Features:
- Mount Style = Flanged
- Switch Type = DPST

Configuration Features:
- Extender Options = None
- Fuse Options = Dual
- Fuse Holder Type = Selectable

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Approved Standards = UL Recognized, CSA Certified, VDE Approved

Conditions for Usage:
- Need Min Size With IEC Connector = Yes
- Need Optional Switch, Fusing, Or Voltage Selector = Yes

Operation/Application:
- Application = General Purpose

Other:
- Brand = Corcom
- Facility Installation = No