

Cable tie - PKB 100X2,5 BK - 1005512

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable tie, resistant to UV rays, dimensions: L x W, 100 x 2.5 mm, color: black

Product Features

- With the UNIFOX-CT ... cable binder tool, the cable binders can be easily tightened and cut off in one step
- The plastic cable binders are ideal for use with WMTB, KMK 2, and KMK 4 cable markers from Phoenix Contact
- UV stabilized (black), for use in outdoor systems
- The cable binders can be used indoors and outdoors even under unfavorable industrial conditions
- For bundling control lines and cables
- Transparent, for standard applications

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	1000 pc
GTIN	 4 017918 012588
Weight per Piece (excluding packing)	0.32 g
Custom tariff number	39269097
Country of origin	United States

Technical data

Dimensions

Length (b)	100 mm
Width (a)	2.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Color	black
-------	-------

Cable tie - PKB 100X2,5 BK - 1005512

Technical data

General

Components	Halogen-free
Flammability rating according to UL 94	V2
Material	PA

Standards and Regulations

Resistance to UV radiation	yes
Flammability rating according to UL 94	V2

Classifications

eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702
eCl@ss 8.0	27140702

ETIM

ETIM 2.0	EC000046
ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703