



- Clamp ties are used to attach a bundle to another surface such as a control panel wall or ceiling using another fastener.
- The design allows for bundling before or after screwing clamp in place.

|                               |  |
|-------------------------------|--|
| Part Number:                  | PLC1.5I-S8-C0                                  |
| Product Family:               | <i>Pan-Ty</i> ® Clamp Ties - Weather Resistant |
| Product Line:                 | Clamp Cable Ties                               |
| RoHS Compliancy Status:       | Compliant                                      |
| Part Description:             | Clamp Tie, 6.1", Intermediate cross section    |
| Product Type:                 | Cable Ties                                     |
| Material:                     | Weather Resistant Nylon 6.6                    |
| Color:                        | Black  |
| CSA Certified:                | Yes  |
| UL Listed (File #E56854):     | No   |
| UL Recognized (File #E56854): | Yes  |
| Length (In.):                 | 6.1  |
| Length (mm):                  | 155  |

|                                    |              |
|------------------------------------|--------------|
| Width (In.):                       | .135         |
| Width (mm):                        | 3.4          |
| Boss Height (In.):                 | .166         |
| Boss Height (mm):                  | 4.2          |
| Boss Width (In.):                  | .335         |
| Boss Width (mm):                   | 8.5          |
| CE Compliant:                      | Yes          |
| Cross Section:                     | Intermediate |
| Locking Style:                     | Locking      |
| Material Flammability Rating:      | UL94V-2      |
| Max. Bundle Diameter (In.):        | 1.25         |
| Max. Bundle Diameter (mm):         | 32           |
| Max. Continuous Use Temperature:   | 185°F (85°C) |
| Metric Screw Size:                 | M4           |
| Min. Loop Tensile Strength (Lbs.): | 40           |
| Min. Loop Tensile Strength (N):    | 178          |
| Nominal Hole Diameter (In.):       | .174         |
| Nominal Hole Diameter (mm):        | 4.4          |
| Screw Size:                        | #8           |

|                  |                                  |
|------------------|----------------------------------|
| Std. Pkg. UOM:   | PK                               |
| Thickness (In.): | .045                             |
| Thickness (mm):  | 1.1                              |
| Tool:            | GTS, GTSL, GS2B, PTS, PPTS, STS2 |
| UOM:             | PC                               |
| Std. Pkg. Qty.:  | 100                              |
| Min. Order Qty.: | 100                              |