PHŒNIX CONTACT

Starter kit - PLC-LOGIC-STARTERKIT1 - 2905504

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PLC logic starter kit 1, consists of: plug-in basic logic module, eight relay output terminal blocks with push-in connection (250 V AC/DC, max. 6 A), micro-USB programming cable, LOGIC+ software, "PLC logic quick start guide" poster

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356959339
Weight per Piece (excluding packing)	660.000 g
Custom tariff number	85371098
Country of origin	Germany

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Articles in set

Controller - PLC-V8C/PT-24DC/BM - 2905135

PLC logic basic logic module, generation 1, with 16 I/Os, can be plugged onto 8 digital PLC-INTERFACE terminal blocks, can be extended to 48 I/Os, realtime clock, accommodates memory module and Bluetooth adapter (firmware update required, see downloads), Push-in connection

PHŒNIX CONTACT

Starter kit - PLC-LOGIC-STARTERKIT1 - 2905504

Articles in set

Relay Module - PLC-RPT- 24DC/21 - 2900299

PLC-INTERFACE, consisting of PLC-BPT.../21 basic terminal block with push-in technology and plug-in miniature relay with power contact, for mounting on NS 35/7,5 DIN rails, 1 PDT, input voltage: 24 V DC

Connecting cable - CAB-USB A/MICRO USB B/2,0M - 2701626

Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

Classifications

eCl@ss

eCl@ss 5.1	27242219
eCl@ss 6.0	27242219
eCl@ss 7.0	27242219
eCl@ss 8.0	27242219
eCl@ss 9.0	27242219

ETIM

ETIM 5.0	EC002581
ETIM 6.0	EC002581

UNSPSC

UNSPSC 13.2	39122329