

Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Catalog Cut Sheet
  - PDFPMNF13R-C P
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'PMNF2-6R-L'

Your search criteria matched only one product, shown below

**PMNF2-6R-L**



- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Maximum insulation temperature 221°F (105°C)
- Rated up to 600 V

Part Number	PMNF26R-L
RoHS Compliancy Status	Compliant
Note	PMNF26R-L replaces PMNF26R-C
Part Description	Metric ring terminal, 1.5– 2.5mm <sup>2</sup> wire range, M6 stud size, nylon barrel insulated, funnel entry.
Product Type	Terminals- Metric
Length (mm)	26.5
Width (mm)	10.9
CE Compliant	No
Clearance (mm)	10.7
Insulation	Nylon
Max. Ins. (mm)	4.11
Panduit Color Code	Blue
Plating Type	Tinned
Pricing Description	Metric Ring Terminal, funnel entry, nylon insulated, 1.5 2.5mm <sup>2</sup> wire range, M6 stud size
Stud Size	M6
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-1550, CT-2500
Wire Range (mm <sup>2</sup> )	1.5 – 2.5
Wire Strip Length (In.)	7/32
Wire Strip Length (mm)	5.6
Min. Order UOM	PC
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.