


KEMET Part Number: PMR205AC6470M470R30
(P405CJ474M125AH471)

KEMET
a YAGEO company

PMR205/P405, Film, Metallized Paper, Resistor/Capacitor, 0.47 uF, 20%, 250 VDC, 85°C, Lead Spacing = 20.3mm



Dimensions

| | |
|----|-----------------|
| L | 24mm MAX |
| H | 15mm MAX |
| T | 9mm MAX |
| S | 20.3mm +/-0.4mm |
| LL | 30mm +5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|---------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 200 |

General Information

| | |
|-------------------|--|
| Series: | PMR205/P405 |
| Dielectric: | Metallized Paper |
| Style: | Radial |
| Features: | RC Unit not approved |
| RoHS: | Yes |
| Lead: | Wire Leads |
| AEC-Q200: | No |
| Construction: | Molded |
| Component Weight: | 4.5 g |
| Miscellaneous: | Resistor Tolerance: +/-30%. Resistor= 470 Ohms. |

Specifications

| | |
|------------------------|-------------|
| Capacitance: | 0.47 uF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 125 VAC |
| Voltage DC: | 250 VDC |
| Temperature Range: | -40/+85°C |
| Rated Temperature: | 85°C |
| Insulation Resistance: | 2.128 GOhms |
| Safety Class: | X2 |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET
a YAGEO company