

[Home](#) / [Panel Mount Indicators](#) / [LED Panel Mount Indicator Red .312" 12V Wire Leads](#)

LED Panel Mount Indicator Red .312" 12V Wire Leads

SKU: PMRL200W-BR12H

Categories: [Panel Mount Indicators](#), [LED Panel Mount Indicator](#), [PMRL200 Series](#)

Product Description

0.312" (9.73mm) LED Panel Indicator
 LED indicator with reflective recessed bezel, single or bi-color LED Voltage: 2V–120V, water-tight option.
 Maximum panel thickness: .160" (PMRL200), .100" (PMRL200, water-tight)
 Recessed bezel LED
 Reflective chrome plated bronze body
 Terminals: Bi-pin or wire leads (6" wire leads, 24 AWG)
 Mounts with hex nut and washer (included)
 Suitable for high vibration applications



Description	Stock Availability	Technical Downloads
<h3>Additional Information</h3>		
Terminals	Wire Leads	
LED size	5mm (T-1 3/4)	
PMI Shape	Round	
Mounting Hole Dimension	Dia. 0.312"	
PMI Mounting	Front Panel Mounting	
PMI Type	Threaded	
Mounting Type	Front Panel Mount	
PMI Color	Red	
PMI Lens Color	–	
LED Output Color	Red	
Lens Type	–	
Lamp Type	LED	
Lamp Life	–	
Viewing Angle	60 degree viewing angle	
Luminous Intensity Typ. (mcd)	14 mcd	
Peak Wavelength (nm)	635 nm	
Voltage	12 VDC	
LED Voltage Forward Typ. (V)	12.0 V	
LED Voltage Forward Min. (V)	12 V	
LED Voltage Forward Max. (V)	14 V	
Operation Supply Voltage	12V	
Rated Current	20 mA	
Tab Terminal Size	–	
Wire Gauge	24 AWG	
PMI Housing Finish	Polished Chrome	
Bezel Finish	No Bezel	
Material Lens	–	
Gasket Material	–	
PMI Panel Thickness	Up to 0.160"	
MSL Rating	–	
Mounting Hardware	With Lockwasher and Hex Nut	
Mounting Hardware Included	Yes	
Accessory	–	
RoHS	Yes	
REACH Compliant	Yes	
Conflict Mineral Free	Yes	
Harmonization Code	8531.80.90.51	
ECCN	EAR99	
Country of Origin	MX (Mexico)	
Product Status	Active	