

Products > Automation and control > Protection relays > Voltage monitoring relays > Three-phase system, without neutral > [Minimum AC voltage and asymmetry. Phase loss and incorrect phase sequence](#)

PMV60A600


VOLTAGE MONITORING RELAY FOR THREE-PHASE SYSTEM, WITHOUT NEUTRAL, MINIMUM AC VOLTAGE AND ASYMMETRY. PHASE LOSS AND INCORRECT PHASE SEQUENCE, 600VAC 50/60HZ



Add to cart

Order code	PMV60A600
Weight [g]	140
Qty. per package	1
Multiple qty. of packs per order	1
Package dimensions [mm]	095X040X075
Volume [cm ³]	285
Bar code [EAN13]	8013975154649
HS Code	85364900

Dimensions



Certifications:

cULus
EAC

Conformity:

IEC/EN 60255-5
IEC/EN 61000-6-2
IEC/EN 61000-6-3
UL 508
CSA C22.2 n° 14

Downloads

Catalogue

Chap. 18 - Protection relays
18 January 2016



Brochures

Protection relays PM series
PD050 September 2009




Technical instructions

True RMS 3-phase multifunction protection relay
PMV30, PMV40, PMV50, PMV60, PMV70
I161 October 2012



2D drawings

 PMV60A600
[2d_PMV60A600](#)


3D drawings

 PMV60A600
[3d_PMV60A600](#)

Certifications

 EC declarations
[CE081-2016_1](#)



 cULus declaration
[E93601](#)



www.lovatoelectric.com uses cookies to enhance your experience and improve website quality. Click [here](#) for more information

I accept