


Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Catalog Cut Sheet
  - PDFPN146RX-C P
  - Part Drawings
  - PDFRing Termina..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'PN14-14RX-L'

Your search criteria matched only one product, shown below

**PN14-14RX-L**



- Expanded wire entry designed to accommodate wire with a larger insulation thickness
- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B
- ‡UL and CSA approved tooling/product combinations.

▪ Part Number	PN1414RX-L
▪ RoHS Compliancy Status	Compliant
▪ Note	PN1414RX-L replaces PN1414RX-C
▪ Part Description	Ring Terminal, 16- 14 AWG, 1/4" stud size, nylon insulated, expanded insulation for large wire O.D.
▪ Product Type	Terminals
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Length (In.)	1.13
▪ Length (mm)	28.7
▪ Width (In.)	0.46
▪ Width (mm)	11.7
▪ CE Compliant	No
▪ Clearance	0.38
▪ Clearance (mm)	9.7
▪ Insulation	Nylon
▪ Max. Ins.	0.200
▪ Max. Ins. (mm)	5.1
▪ Panduit Color Code	Blue
▪ Plating Type	Tinned
▪ Pricing Description	Ring Terminal, expanded nylon insulation, 16 14 AWG, 1/4" stud size
▪ Stock	0.03
▪ Stock (mm)	0.8
▪ Stud Size	1/4"
▪ Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
▪ Tool	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡
▪ Wire Range	16 – 14 AWG
▪ Wire Range (mm <sup>2</sup> )	1.0 – 2.5
▪ Min. Order UOM	PC
▪ Min. Order Qty.	50
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.