



**RoHS
Compliant**

Specifications

Electrical

Rated Voltage : 300V
 Conductor Resistance : 88.9Ω/KM At 20°C
 Insulation Resistance : 2.5MΩ/KFT At 20°C
 Temperature : -20°C to +105°C

Construction

Conductor Size : 24AWG
 Construction : 7/0.2±0.008mm
 Material : Stranded Tinned Copper


Insulation

Colour : Brown, Red, Orange, Yellow, Green, Blue, Purple, Grey, White and Black
 Material : 90A PVC
 Diameter : 1.1 ±0.1mm

Sheath

Material : 91A PVC
 Overall Diameter : $1.4 \pm 0.15 \text{mm} * \{(N-1) * 2.54 + 1.4 \pm 0.4 \text{mm}\}$
 Temperature : 25°C ±5°C, 60% to 70% Humidity
 Humidity : 60% to 70%
 Length : Available in 50m or per meter

Diagram



Part Number Table

Description	Part Number
Ribbon Cable, 2.54mm, 24AWG, 4 Core	PP002605
Ribbon Cable, 2.54mm, 24AWG, 6 Core	PP002606
Ribbon Cable, 2.54mm, 24AWG, 8 Core	PP002607
Ribbon Cable, 2.54mm, 24AWG, 10 Core	PP002608

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
 Farnell.com/exclusive-brands
 Element14.com/exclusive-brands