


 Current refinements (click to remove)

 [Region](#) [USA](#) [Product Line](#) [Cable Ties](#) [Nylon Cable Ties](#) [Nylon Cable Ties](#) [Product Family](#)
Pan-Ty® Releasable Cable Ties - Weather Resistant


- The extended tab end of releasable cable ties permits easy release and reuse even after tie has been pulled up snug by hand.
- Releasable ties are particularly useful in harnessing where changes are anticipated during development production or servicing in the field.
- To release grasp the head of the cable tie, deflect release tab, and pull the cable tie away from the bundle.

Related Products

- [Push Barb Cable Tie Mounts](#)
- [Push Mounts](#)
- [Push Button Mount](#)
- [Epoxy Applied Mounts](#)
- [Epoxy Applied Swivel Mount](#)
- [Epoxy Applied Cable Tie Mount Kits](#)
- [More...](#)

See Also

- [Cable Tie Tools to Speed Your Installation](#)

Part Number	PRT3S-M0
Product Family	Pan-Ty® Releasable Cable Ties - Weather Resistant
RoHS Compliant	Compliant
Part Description	Cable Tie, Releasable, 11.5", Standard cross section
Product Type	Cable Ties
Material	Weather Resistant Nylon 6.6
Color	Black
CSA Certified	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Length (In.)	11.5
Length (mm)	292
Width (In.)	.190
Width (mm)	4.8
CE Compliant	Yes
Cross Section	Standard
Head Height (In.)	.219
Head Height (mm)	5.6
Head Width (In.)	.337
Head Width (mm)	8.6
Locking Style	Releasable
Material Flammability Rating	UL94V-2
Max. Bundle Diameter (In.)	3.00
Max. Bundle Diameter (mm)	76
Max. Continuous Use Temperature	185°F (85°C)
Min. Loop Tensile Strength (Lbs.)	50
Min. Loop Tensile Strength (N)	222
Std. Pkg. UOM	PK
Thickness (In.)	.052
Thickness (mm)	1.3

Tool	Hand Installed Only
UOM	PC
Std. Pkg. Qty.	1000
Min. Order Qty.	1000
BOM Qty. (# of Pkgs.)	

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2006, PANDUIT CORP. All rights reserved.