

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# 12-Outlet Vertical Power Strip, 120V, 20A, Hardwired Input, 36 in.

MODEL NUMBER: PS3612-20HW



### **Highlights**

- AC input hardwired via knockout on unit
- 12 outlets
- 20-amp capacity
- Ideal for applications requiring permanent installation

#### **Package Includes**

- PS3612-20HW
- · Instruction manual

#### Description

Tripp Lite's PS3612-20HW Power Strip offers 20 amp multi-outlet AC power distribution in a convenient 36 inch hardwire cabinet. Includes knockout panels to accept 3/4 in. conduit fittings for hardwire installation and 12 output receptacles with 2.99 inch center-to-center spacing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications.

INPUT/OUTPUT: Input: Hardwire access via knockout panels that accept 3/4 inch conduit fittings

Output: 12 Outlets total (2 NEMA 5-15/20R and 10 NEMA 5-15R)

ELECTRICAL: 120V AC, 50/60Hz, 20A (no circuit breaker)

FORMAT: 36 inch strip format

#### **Features**

- · Versatile all-metal 36 inch format with outlets arranged in a single row
- Knockout panels for 3/4 inch conduit fittings allow permanent hardwire installation
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- 12 outlets total: 2 NEMA 5-15/20R (20A) and 10 NEMA 5-15R (15A)
- 20 amp electrical capacity
- 120VAC, 50/60Hz electrical compatibility

## **Specifications**

OUTPUT	
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(2) 5-15/20R; (10) 5-15R
Output (Watts)	2400





Outlet Spacing	2.99 in.	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	20A 120V	
Input Connection Type	Hardwire	
Input Cord Length (ft.)	0	
Input Cord Length (m)	0.00	
Voltage Compatibility (VAC)	120	
PHYSICAL		
Unit Dimensions (hwd / in.)	36 x 1.5 x 1.5	
Unit Dimensions (hwd / cm)	91.44 x 3.8 x 3.8	
Material of Construction	Metal	
Integrated Keyhole Mounting Tabs	Mount through housing supports bolt down installation to a variety of flat surfaces	
Receptacle Color	Almond	
Outlets Measurement (Center to Center)	101.60mm	
CERTIFICATIONS		
cUL / CSA (Canada)	cUL	
Approvals	UL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies