

Insulating sleeve - PS-IH BK - 0311634

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Insulating sleeve, Color: black

Product Features

- The test plug reliably makes contact in the bridge shaft and in all test sockets with a 2.3 mm or 4 mm diameter
- Individual test adapters can be combined using the modular PS-...2,3MM test plug.

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 001575
Weight per Piece (excluding packing)	0.68 g
Custom tariff number	85472000
Country of origin	Germany

Technical data

Dimensions

Height	15.00 mm
Length	6 mm
Width	6 mm
Pin diameter	6.50 mm

General

Color	black
Ambient temperature (operation)	-40 °C ... 100 °C

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Insulating sleeve - PS-IH BK - 0311634

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27141190
eCl@ss 6.0	27141190
eCl@ss 7.0	27141190
eCl@ss 8.0	27440313

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000448
ETIM 5.0	EC002255

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC
