

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDF Ring Termina ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'PV10-610RB-2K'

Your search criteria matched only one product, shown below

PV10-610RB-2K



The PVC insulation forms an insulation crimp on the wire insulation. All polyvinylchloride 2 - piece insulated terminals are rated at 600 volts and designed for up to 105° C (221° F) operating temperature.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Teardrop shaped mounting hole of multiple stud terminals permits use with #6, #8, or #10 size studs
- Ring tongue design assures a secure connection in high vibration applications
- Insulation support helps to prevent wire damage in bending applications
- Maximum insulation temperature 221°F (105°C)
- UL and CSA rated up 600 V per UL 486

Part Number	PV10-610RB-2K
RoHS Compliancy Status	Compliant
Part Description	Multiple Stud Ring Terminal for #6, #8 and #10 stud sizes. Wire range of #12- 10 AWG.
Product Type	Terminals- Reel Fed
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.17
Width (In.)	.37
Barrel to Hole Length (In.)	.89
CA-800 Series Crimp Die	CD-800-3
CA9 Series Crimp Die	CD9-3B
CE Compliant	No
CE Marking	No
Clearance	.31
Max. Ins.	.225
Panduit Color Code	Yellow
Pieces Per Reel	2000
Pricing Description	Ring Terminal, MultStud #6, #8, #10, vinyl insulated, 12- 10 AWG, funnel entry
Stock	.04
Stud Size	#6, #8, #10
Wire Range	12 – 10 AWG
Wire Range (mm ²)	2.5 – 6.0
Min. Order UOM	PC
Min. Order Qty.	2000
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.