QOU130

Mini circuit breaker, QOU, 30A, 1 pole, 120/240 VAC, 10kA





Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

Line Rated Current	30 A	
Electrical connection	Slotted box lugs, line side	
	Slotted box lugs, load side	
[Ue] rated operational voltage	120/240 V AC	
	120 V AC	
	48 V DC	
Mounting mode	Unit mount	
AWG gauge	AWG 14AWG 2 aluminium/copper	
Height	4.05 in (102.87 mm)	
Depth	2.95 in (74.93 mm)	
Maximum Width	0.75 in (19.05 mm)	
Tightening torque	45 lbf.in (5.08 N.m) AWG 14AWG 2)	

Environment

Product certifications	CSA UL Listed
	IEC

Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901418566
Nbr. of units in pkg.	40
Package weight(Lbs)	0.37 lb(US) (0.17 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	0.90 in (2.286 cm)
Package 1 width	3.10 in (7.874 cm)
Package 1 Length	4.50 in (11.430 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty 18 months	
--------------------	--