

$\phi d \pm 0.05$	$p = 10$	$p = 15$	$15 < p \leq 27.5$	$p = 37.5$
	0.6	0.6 or 0.8*	0.8	1

* See size table.
All dimensions are in mm.

GENERAL TECHNICAL DATA

Dielectric: polypropylene film.
Plates: metal layer deposited by evaporation under vacuum.
Winding: non-inductive type.
Leads: tinned wire.
Protection: plastic case, thermosetting resin filled. Box material is solvent resistant and flame retardant according to UL94 V0.
Marking: Manufacturer's logo, series, capacitance, tolerance, rated voltage, capacitor class, dielectric code, climatic category, passive flammability category, manufacturing date code, approvals, manufacturing plant.
Climatic category: 40/110/56 IEC 60068-1

Operating temperature range: -40 to +110°C
Related documents: IEC 60384-14, EN 60384-14.

ELECTRICAL CHARACTERISTICS

Rated voltage (V_R): 300Vac / 1000Vdc; 50/60Hz
Capacitance range: 1000pF to 1.0µF
Capacitance values: E6 series (IEC 60063 Norm).
Capacitance tolerances (measured at 1 kHz):
 ±10% (K); ±20% (M).

Dissipation factor (DF):
 $tg\delta \times 10^{-4}$ at +25°C ±5°C: ≤20 (15)* at 1kHz
 * Typical value

Insulation resistance:
Test conditions
 Temperature: +25°C ±5°C
 Voltage charge time: 1 min
 Voltage charge: 100 Vdc
Performance
 ≥1 x 10⁵ MΩ (5 x 10⁵ MΩ)* for C ≤0.33µF
 ≥30000 s (150000 s)* for C >0.33µF
 * Typical value

Test voltage between terminations (on all pieces):
 2500Vac for 1 s + 5000Vdc for 1 s at +25°C ±5°C

Y2 / X1 CLASS (IEC 60384-14) MKP Series METALLIZED POLYPROPYLENE FILM CAPACITOR SELF-HEALING PROPERTIES

Typical applications: Interference suppression and «across-the-line» applications. Suitable for use in situations where failure of the capacitor could lead to danger of electric shock.
PRODUCT CODE: R41

Note: R.41 series has replaced the R73 series (available only upon request). For new design we suggest the use of the R.41 series.

Pitch (mm)	Box thickness (B) (mm)	Maximum dimensions (mm)		
		B max	H max	L max
10.0	All	B +0.2	H +0.1	L +0.2
15.0	<7.5	B +0.2	H +0.1	L +0.3
15.0	≥7.5	B +0.2	H +0.1	L +0.5
22.5	All	B +0.2	H +0.1	L +0.3
27.5	All	B +0.2	H +0.1	L +0.3
37.5	All	B +0.3	H +0.1	L +0.3

TEST METHOD AND PERFORMANCE

Damp heat, steady state:

Test conditions
 Temperature: +40±2°C
 Relative humidity (RH): 93 ±2%
 Test duration: 56 days

Performance
 Dielectric strength: no dielectric breakdown or flashover at 1500Vac/1 min
 Capacitance change $|\Delta C/C|$: ≤5%
 Insulation resistance: ≥50% of initial limit.

Endurance:

Test conditions
 Temperature: 110°C ±2°C
 Test duration: 1000 h
 Voltage applied: 1.7 x V_R + 1000Vac 0.1 s/h

Performance
 Dielectric strength: no dielectric breakdown or flashover at 1500Vac/1 min
 Capacitance change $|\Delta C/C|$: ≤10%
 Insulation resistance: ≥50% of initial limit.

Resistance to soldering heat:

Test conditions
 Solder bath temperature: +260°C ±5°C
 Dipping time (with heat screen): 10 s ±1 s
Performance
 Capacitance change $|\Delta C/C|$: ≤2%

APPROVALS

	ENEC IEC 60384-14	Class Y2 / X1	File No. V4160
	CSA C22.2 N°1 (250Vac)	Across-the-line	File No. LR83890
	UL 1414 (.85°C; 250Vac)	Across-the-line	File No. E 97797
	GB IT 14472	Class Y2 / X1	File CQC3001006820 CQC3001006821

Approved according to IEC 60384-14 (ex-former EN 132400)
 According to IEC 60065.


(*) ENEC mark has replaced all the following European National marks:



Y2 / X1 CLASS (IEC 60384-14) MKP Series
METALLIZED POLYPROPYLENE FILM CAPACITOR
 SELF-HEALING PROPERTIES

Typical applications: Interference suppression and across-the-line applications. Suitable for use in situations where failure of the capacitor could lead to danger of electric shock.
PRODUCT CODE: R41

Rated Cap.	300 Vac/1000Vdc Std dimensions				Ø d	Max dv/dt at 420Vdc (V/µs)	Part Number
	B	H	L	p			
1000 pF	4.0	9.0	13.0	10.0	0.6	800	R413F 1100 -- 00 -
1500 pF	4.0	9.0	13.0	10.0	0.6	800	R413F 1150 -- 00 -
2200 pF	4.0	9.0	13.0	10.0	0.6	800	R413F 1220 -- 00 -
3300 pF	5.0	11.0	13.0	10.0	0.6	800	R413F 1330 -- 00 -
4700 pF	5.0	11.0	13.0	10.0	0.6	800	R413F 1470 -- M1 -
4700 pF	6.0	12.0	13.0	10.0	0.6	800	R413F 1470 -- 00 -
6800 pF	6.0	12.0	13.0	10.0	0.6	800	R413F 1680 -- 00 -
3300 pF	5.0	11.0	18.0	15.0	0.6	600	R413I 1330 -- 00 -
4700 pF	5.0	11.0	18.0	15.0	0.6	600	R413I 1470 -- 00 -
6800 pF	5.0	11.0	18.0	15.0	0.6	600	R413I 1680 -- 00 -
0.010 µF	5.0	11.0	18.0	15.0	0.6	600	R413I 2100 -- 00 -
0.015 µF	6.0	12.0	18.0	15.0	0.6	600	R413I 2150 -- 00 -
0.022 µF	7.5	13.5	18.0	15.0	0.6	600	R413I 2220 -- 00 -
0.033 µF	8.5	14.5	18.0	15.0	0.6	600	R413I 2330 -- 00 -
0.047 µF	10.0	16.0	18.0	15.0	0.8	600	R413I 2470 -- 00 -
0.047 µF	6.0	15.0	26.5	22.5	0.8	500	R413N 2470 -- 00 -
0.068 µF	7.0	16.0	26.5	22.5	0.8	500	R413N 2680 -- 00 -
0.10 µF	10.0	18.5	26.5	22.5	0.8	500	R413N 3100 -- 00 -
0.15 µF	11.0	20.0	26.5	22.5	0.8	500	R413N 3150 -- 00 -
0.22 µF	13.0	22.0	26.5	22.5	0.8	500	R413N 3220 -- 00M
0.22 µF	13.0	22.0	32.0	27.5	0.8	400	R413R 3220 -- 00 -
0.33 µF	14.0	28.0	32.0	27.5	0.8	400	R413R 3330 -- 00 -
0.47 µF	18.0	33.0	32.0	27.5	0.8	400	R413R 3470 -- 00 -
0.68 µF	18.0	33.0	32.0	27.5	0.8	400	R413R 3680 -- 00 -
0.47 µF	13.0	24.0	41.5	37.5	0.8	300	R413W3470 -- 00 -
0.68 µF	16.0	28.5	41.5	37.5	0.8	300	R413W3680 -- 00 -
1.0 µF	20.0	40.0	41.5	37.5	0.8	300	R413W4100 -- 00 -

Mechanical version and packaging (Table1) 
 Tolerance: K (±10%); M (±20%)

E12 Series available upon request
 All dimensions are in mm.

Table 1

Standard packaging style	Lead length (mm)	Taping style			Ordering code (Digit 10 to 11)
		P ₂ (mm)	Fig. (No.)	Pitch (mm)	
AMMO-PACK		12.70	1	10.0/15.0	DQ
AMMO-PACK		19.05	2	22.5	DQ
REEL Ø 500mm		12.70	1	10.0/15.0	CK
REEL Ø 500mm		19.05	2	22.5/27.5	CK
Loose, short leads	4 ⁺²				00
Loose, long leads (p=10mm)	25 ^{±1}				JY
Loose, long leads (p=15mm)	25 ^{+2/-1}				50
	30 ⁺⁵				40

Note: Ammo-pack is the preferred packaging for taped version