



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided equipment	All required connectors Battery recycling guide Metallic battery tray or enclosure Reusable packaging Installation guide
--------------------	--

Physical

Depth	20.98 in (53.3 cm)
Height	2.99 in (7.6 cm)
Net Weight	42.09 lb(US) (19.09 kg)
Maximum Width	8.50 in (21.6 cm)

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery voltage	48V
Battery type	Lead-Acid battery
RBC Quantity	1

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304218463
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	9.02 in (22.9 cm)
Package 1 width	15.51 in (39.4 cm)
Package 1 Length	30.24 in (76.8 cm)
Number of Units in Package 3	12

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	ENERGY STAR UPS V1.0 (USA)
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	1 year repair or replace, 30 days (Japan only)
----------	--