

## Reducing bridge - RB PTPOWER 35-ST 16 - 3032170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing bridge, for bridging of PTPOWER 35 to ST or PT ..N terminal blocks with 16 mm<sup>2</sup> nominal cross section, Pitch: 14.5 mm, Length: 5 mm, Width: 22.9 mm, Number of positions: 2, Color: red

The figure shows a similar product

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	 4 055626 012353
GTIN	4055626012353
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85389099
Country of origin	Poland

### Technical data

#### Technical data

Color	red
Material	PA 6.6
Number of positions	2
Pitch	14.5 mm
Width	22.9 mm
Height	54.4 mm
Length	5 mm
Flammability rating according to UL 94	V0
Maximum load current	90 A

# Reducing bridge - RB PTPOWER 35-ST 16 - 3032170

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

### ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489
ETIM 6.0	EC000489

### UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426