

Reducing adapter - REDUC-M-KV-M25/M20 - 1647624


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Step-down adapter, M25 to M20, including O-ring



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 941529
Weight per Piece (excluding packing)	18.4 g
Custom tariff number	74153300
Country of origin	Germany

Technical data

Dimensions

Length	10 mm
Length without connecting thread	3 mm
Connecting thread diameter	25 mm
Hexagon angular dimension GRP	30 mm
Length of the connecting thread	7 mm

Ambient conditions

Degree of protection	IP65 (Depends on the screw connection used)
Ambient temperature (operation)	-20 °C ... 80 °C

General

Material	Nickel-plated brass
Cable gland material	Nickel-plated brass

Reducing adapter - REDUC-M-KV-M25/M20 - 1647624

Technical data

General

O-ring material	NBR
Outer thread	M25
Internal thread	M20
Color	silver

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27439207

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000938

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

Drawings

Reducing adapter - REDUC-M-KV-M25/M20 - 1647624

Dimensional drawing

