

5-Wire M12 *eurofast*® Cordsets, Standard Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>RK ..**</p>	RK 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50543-*M [†]	<i>flexlife</i> ®	
	RK 4.5T-*/S90	AWM PUR Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50649-*M [†]	<i>Cut/Abrasion Immune</i>	
	RK 4.5T-*/S101	AWM TPE Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50909-*M [†]	<i>flexlife-10, High Flex Over 10 Million Cycles</i>	
<p>RKK ..**</p>	RK 4.5T-*/S618	AWM PVC Grey 5x22 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50609-*M [†]	<i>RFI/EMI Protection</i>	
	RK 4.5T-*/S715	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50684-*M [†]	<i>flexlife</i>	
	<p>RKV ..**</p>	RK 4.5T-*/S653	AWM PVC Grey 4x22 AWG Foil/Drain 105°C 5.2 mm OD Cable #RF50577-*M [†]	
RK 4.5T-*/S1554		AWM PVC Black 5x22 AWG Foil/Drain 105°C 5.2 mm OD Cable #RF50794-*M [†]	<ol style="list-style-type: none"> 1. BN 2. WH 3. BU 4. BK 5. GY 	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RK .."; "RKK .." indicates nylon and "RKV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.