

4-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	RKC 4.4T-*	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579-*M†	flexlife®	
	RKC 4.4T-*/S90	AWM PUR Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50544-*M†	Cut/Abrasion Immune	
	RKC 4.4T-*/S622	AWM PVC Grey 4x18 AWG 105°C 7.3 mm OD Cable #RF50580-*M†	flexlife	
	RKC 4.4T-*/S824	PLTC PVC Grey 4x18 AWG 105°C 7.2 mm OD Cable #RF50844-*M†	Tray Rated	
	RKC 4.4T-*/S1587	AWM TPE Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50956-*M†	Weld Flash Immune	
	RKC 4.4T-*/S101/S849	AWM TPE Grey 4x22 AWG 105°C 5.7 mm OD Cable #RF50941-*M†	flexLife-10, High Flex Over 10 Million Cycles	
	RKC 4.4T-*/S101	AWM TPE Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50968-*M†		
	RKC 4.4T-*/S1062	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579-*M†	flexlife® Cable, PVC plug body with PVC contact carriers	

Cordsets

1. BN
2. WH
3. BU
4. BK

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKC .."; "RKC V .." indicates 316 stainless steel.
 † See Section N for reelfast® cable information.