

WIRE MANAGEMENT PRODUCTS

LIQUID-TIGHT CONNECTORS

SLC, RLC

UL LISTED
CSA CERTIFIED

CHOOSE LIQUID-TIGHT CONNECTORS FOR:

- Liquid-Tight Environmental Seal
- Oil and Solvent Resistance
- Quick Re-entry for Cable Repair or Re-routing

LIQUID-TIGHT CONNECTOR APPLICATIONS:

- Complete Conduit Connection System for Fiber Optic Cable, Wire Harnesses and Flexible Cable Products

CHARACTERISTICS

COLOR DESCRIPTION:

- All Standard Packages: Black

PHYSICAL PROPERTIES:

- Suitable for Both Indoor and Outdoor Use
- Flammability: UL 94V-2

CHEMICAL PROPERTIES:

- Corrosion Resistant
- Resists Solvents, Oil, Grease, Alcohol, Gasoline, Weak Acids and Salt Water

SPECIFICATIONS

- UL Listed
- CSA Certified (except for 1/4" size)



Certified
Canadian Standards Association



ALPHA'S STRAIGHT (SLC) AND RIGHT-ANGLE (RLC) LIQUID-TIGHT NON-METALLIC CONNECTORS are designed to connect with Alpha's routing system products to insure liquid-tight integrity. Alpha's electrical, black PVC flexible tubing (FNT) matches black straight or right-angle connectors.



STRAIGHT CONNECTORS (SLC)				RIGHT-ANGLE CONNECTORS (RLC)			
Alpha Part No.	Trade Size Inches	Thread Size	Standard Put-Ups (Each)	Alpha Part No.	Trade Size Inches	Thread Size	Standard Put-Ups (Each)
SLC-1/4†	1/4"	—	10, 100	RLC-3/8	3/8"	1/2 NPT	10, 100
SLC-3/8	3/8"	1/2 NPT	10, 100	RLC-1/2	1/2"	1/2 NPT	10, 100
SLC-1/2	1/2"	1/2 NPT	10, 100	RLC-3/4	3/4"	3/4 NPT	10, 100
SLC-3/4	3/4"	3/4 NPT	10, 100	RLC-1	1"	1 NPT	10, 100
SLC-1	1"	1 NPT	10, 100				

†SLC-1/4 is a snap-in connector.