

4, 5 and 6-Wire M12 *eurofast*® Cordsets, "S" Style, Shielded

- Straight Male Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout	
	RSS 4.4T-*	AWM PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50729-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK	
	RSS 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C 250 V, 4 A 7.2 mm Cable #RF50810-*M [†]			
	RSS 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50823-*M [†]	RFI/EMI Shielding Tied to Coupling Nut, Tray Cable Rated		
	RSS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50713-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY	
	RSS 6T-*	AWM PVC Grey 6x24 AWG 105°C 60 VAC/75 VDC, 2 A 7.3 mm OD Cable #RF50814-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RSS .."; "RSSV .." indicates 316 stainless steel..

† See Section N for *reelfast*® cable information.

8, 10 and 12-Wire M12 eurofast® Cordsets, "S" Style, Shielded

- Straight Male Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	RSS 8T-*	AWM PVC Grey 8x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50813-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD
	RSS 10T-*	AWM PVC Grey 10x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF51006-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. WH 6. PK 2. BN 7. BU 3. GN 8. RD 4. YE 9. OG 5. GY 10. TN
	RSS 12T-*	AWM PVC Grey 12x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50988-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. WH 7. BU 2. BN 8. RD 3. GN 9. OG 4. YE 10. TN 5. GY 11. BK 6. PK 12. VT

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RSS .."; "RSSV .." indicates 316 stainless steel..
 † See Section N for **reelfast**® cable information.