



RW-200-E-3/4-0-SP Product Details

[Share](#) [Print](#) [Email](#)


RW-200-E-3/4-0-SP

TE Internal Number: CB03394012
✔ Active

Heat Shrink Tubing

✔ Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = RW-200
- Product Source = U.K., U.S.
- Flexible
- Medium Wall Style

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

Feedback

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Heat Shrinkable Tubing
- [Color](#) = Black

Dimensions:

- [Inside Diameter \(Min-Max\) \(mm \[in\]\)](#) = 9.53 - 19.05 [0.375 - 0.750]
- [Expanded ID, Min. \(mm \[in\]\)](#) = 19.10 [0.750]
- [Recovered ID, Max. \(mm \[in\]\)](#) = 9.50 [0.374]
- [Length \(M \[ft\]\)](#) = 30.48 [100.00]

Body Features:

- [Product Name](#) = RW-200
- [Pliancy](#) = Flexible
- [Wall Style](#) = Medium
- [Wall Type](#) = Single
- [Material](#) = Crosslinked Fluoroelastomer
- [Shrink Ratio](#) = 2:1
- [Fluid Type](#) = Aviation Fuel, Brake Fluid, Chemicals/Solvents, Hydraulic Fluid, Lubricating Oil, Water
- [Resistant To](#) = Abrasion, Fluids, Wrinkling

Housing Features:

- [Material Systems](#) = Yes
- [Material Systems Code](#) = 200

Industry Standards:

- [Government/Industry Qualification](#) = No
- [Flammability Rating Type](#) = Highly Flame-Resistant
- [UL Rating](#) = None
- [CSA Certified](#) = No
- [Approved Standards](#) = BS 4G-198 Part 3 12A, DEF Std 59 -97 Issue 3 Type 4A, VDE 0341 Part 9005, VG95343 Part 5E Type D
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Environmental:

- [Fluid Resistance](#) = Splash Protection
- [Operating Temperature \(°C\)](#) = -55 - +200

Conditions for Usage:

- [Full Recovery Temperature \(°C\)](#) = 175
- [Shrink Temperature, Min. \(°C\)](#) = 100
- [High Temperature Compatible](#) = Yes

Operation/Application:

- [Application](#) = Cable Jacketing, Wire Bundling
- [Emission Free](#) = No
- [Product Use](#) = Cables, Harnesses

Packaging Features:

- [Packaging Method](#) = Spool

Product Availability:

- [Product Source](#) = U.K., U.S.

Other:

- [Brand](#) = Raychem

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

