

## Adjustable Mounting Systems

- Provides flexible mounting and positioning of sensors and lights
- Includes 3" and 6" column mounting kits for mounting area lights and backlights
- Features Bogen Arm and clamp for use with *P4* and *Pro* sensors
- Offers 2" mounting knuckle assembly for spot lights



SMBPPLK



SMBPPK6



SMBPPK3



SMBPPF1 &amp; SMBPPFB



## Adjustable Mounting Systems

Used With	Description	Model
Pro P4 Vision Lights	3" Column, Base, and Knuckle Kit	SMBPPK3
	6" Column, Base, and Knuckle Kit	SMBPPK6
	Mounting Bracket Knuckle	SMBPPK
	3" Column	SMBPPKE3
	6" Column	SMBPPKE6
	Mounting Bracket Base	SMBPPKB
	2" Mounting Knuckle Assembly	SMBPPLK
	Bogen Arm with Single Knob	SMBPPF1
	Bogen Arm Clamp	SMBPPFB

## Elevated Use—Stand-off Pipe, Brackets and Adapters

	Description	Length	Model	Used With
	Thermoplastic Acetal adapter and cover (M30 to 1/2" NPSM/DN15)	—	SA-M30TE12	Connects TL50 to 1/2" NPSM/DN15 pipe
	Thermoplastic Acetal adapter and cover (M30 to 1/2" NPSM/DN15)	—	SA-M30E12	Connects K50L & K80L to 1/2" NPSM/DN15 pipe
	Stainless steel pipe (1/2" NPSM/DN15)	150 mm	SOP-E12-150SS	K50L K80L TL50
		300 mm	SOP-E12-300SS	
	Anodized aluminum pipe (1/2" NPSM/D15)	150 mm	SOP-E12-150A	
		300 mm	SOP-E12-300A	
Thermoplastic Acetal mounting base (1/2" NPSM/DN15 to M30)	—	SA-E12M30		
	Stainless steel bracket for wall or other flat surfaces	—	SMBE12USS	SOP-E12-150A SOP-E12-300A SOP-E12-150SS SOP-E12-300SS

## Elevated Use—Enclosure Mounts and Extensions

	Description	Length	Model	Used With
	Thermoplastic Acetal standoff with 30 mm mounting base for cabinet mounting or use with most 30 mm brackets	75 mm	<b>SA-M30M30-75</b>	K50L
	Zinc coated, oversized right-angle legend plate for identification labels	—	<b>SA-30RL55X93</b>	SA-M30M30-75
	Thermoplastic Acetal standoff with 22.5 mm mounting base for cabinet mounting	50 mm	<b>SA-M22M22-50</b>	K30L

Accessories

Brackets



Cordsets

Retroreflectors

Miscellaneous

Reference

## Elevated Use—Hanging Bracket

	Description	Length	Model	Used With
	Zinc coated bracket with strain relief for mounting one device	—	<b>SA-30RL55X93C</b>	K50 Push Button VTB
	Zinc coated bracket for mounting two devices	—	<b>SA-30DRL55X93C</b>	Sensors and indicators with 30 mm base or barrel mount