infrastructure for a conne	UN	TED STATES [C	HANGE] ENGLISH	REGISTER / LOG IN	FOLLOWUS			
PANDUIT	SOLUTIONS	PRODUCTS AND SERVICES	SUPPORT	ABOUT US		Search Panduit.	com	
Search within category BUY NOW DESIGN / INST			StrongHold (SC8-50-S10-C0 StrongHold Cable Tie, Clamp, 7.87L (200mm), #10 Screw, Stanard, Nylon, Weather Resistant Black, Package 100				
		Specs Packaging Deta	ails Documer	nts		Add to Favorites	Add to BOM	
		Material	Nylor	1 6.6				
		Color	Black	(
		Length (In.)	7.87					
		Length (mm)	200.0)				
		Locking Style	Locki	ing				
		Min. Loop Tensile Strength (L	bs.) 50.00)				
		Min. Loop Tensile Strength (N	l) 222					
		CE Compliant	Yes					
		Application	Gene	eral				
		CSACertified	No					
		Continuous Use Temperature Range	e -40°F	⁻ (-40°C) - 185°F ((85°C)			
		Cross Section	Stand	dard				
		Environment	Outdo	oor (UV Resistant	t)			
		Plenum-Rated	No					
		Product Group Assignment	Cable	e Ties				
		Product Type	Cable	e Ties				
		Releasable	0					
		Screw Size	#10					
		Stable to Vibration	No					
		Standards	UL62	2275 Compliant (⁻	Type 1, 11), UL Rec	ognized #E56854		
		Style	Clam	np Ties				
		Sub Brand	Stron	gHold				
		Surface Treatment	Untre	ated				
		Thickness (In.)	0.05					
		Thickness (mm)	1.3					
		Тооі	No To	poling				
		Туре	Onel	Piece Cable Ties				
		Type of fastening	Screv	w Hole				
		UL 62275 Compliant (Type 1,	11) Yes					
		UL 62275 Compliant (Type 2,	21) No					
		UL Listed (File #E56854)	No					
		UL Recognized (File #E56854	4) Yes					
		UNSPSC	3912	1703				

UVResistant	1
Width (In.)	0.19
Width (mm)	4.8
RoHS Compliancy Status	Compliant
Min. Order Qty.	100

LEGAL INFORMATION | PRIVACY POLICY | CONTACT US | SITE MAP | WHERE TO BUY | JOBS | UNSUBSCRIBE