



## SCCLC022XXALXA Product Details

[Share](#) | [Print](#) | [Email](#)


**SCCLC022XXALXA**  
(2-1437469-2)

TE Internal Number: 2-1437469-2

Active

### Time Delay Relays

Not EU RoHS or ELV Compliant

#### Product Highlights:

- SCC Specification Grade Precision Timing Series
- Input Voltage = 120 VAC
- Input Voltage = 120 VDC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC

[View all Features](#)

#### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Mechanical Attachment:

- Mounting Options = Socket

#### Electrical Characteristics:

- Input Voltage (VAC) = 120
- Input Voltage (VDC) = 120
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC

#### Termination Features:

- Termination Type = 11-Pin Octal Style Plug

#### Dimensions:

- Approx. Dimensions (L x W x H) (mm [in]) = 50.00 x 50.00 x 83.00 [1.970 x 1.970 x 3.270]

#### Contact Features:

- Delay Time = 0.33 minutes to 10 minutes
- Type of Control = Knob
- Repeatability, Max. = ± 0.5% +4 msec

#### Configuration Features:

- [Contact - Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

#### Industry Standards:

- [Approved Standards](#) = CE Approved, CSA Certified, FM Approved, UL Listed, UL Recognized
- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- Temperature Range (°C) = -30 - +50

#### Operation/Application:

- Mode of Operation = Interval

#### Other:

- [Series](#) = SCC Specification Grade Precision Timing
- Brand = Agastat
- Comment = Includes 11-pin octal socket.

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed

