

SDSA3650

Surge protection device, Surgelogic, 40kA,
600Y/347 VAC, 3 phase, 4 wire, NEMA 4X



Main

Product	Surge protection device
Range	Surgelogic

Complementary

Surge Current	40 kA per phase
Voltage Rating	600Y/347 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
MCOV	510 V
Nominal Discharge Current	10 kA
SCCR	200 kA
Local Signalling	Status LED green normal operation
Height	3 in (76.20 mm)
Width	3.6 in (91.44 mm)
Depth	3.4 in (86.36 mm)
Cable length	24 in (609.60 mm)

Environment

Enclosure Rating	NEMA 4X
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4 type I NEC 285 type I CSA C22.2 No 8
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	00785901210887
Nbr. of units in pkg.	1
Package weight(Lbs)	0.78 lb(US) (0.35 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.10 in (7.874 cm)
Package 1 width	3.90 in (9.906 cm)
Package 1 Length	5.00 in (12.7 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	21.92 lb(US) (9.943 kg)
Package 2 Height	6.30 in (16.002 cm)
Package 2 width	13.60 in (34.544 cm)
Package 2 Length	20.50 in (52.07 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

