SLM400-KIT Sound Level Meter / Calibrator Kit

Features:

 Includes Type 2 Sound Level Meter with 9V battery, windscreen, plus Sound Level Calibrator with mini screwdriver and 9V battery, stored in a hard carrying case

Sound Level Meter:

- · 35 to 130dB over 2 ranges
- ±1.5db accuracy
- · A and C weighting

Sound Level Calibrator:

- · Selectable fast/slow response time
- · Selectable 94dB and 114dB output at 1kHz
- · Fits 1/2" diameter microphones
- Output Frequency ±4%@1kHz with ±0.5dB accuracy
- · Optional model complete with Certificate of Traceability to N.I.S.T.
- · 1 year warranty

Applications:

 Test and verify sound levels for worker safety (OSHA), community noise ordinances, night clubs/concerts, airports, mines, athletic events, construction sites, vehicle testing, wind farms, new product noise reduction, and other applications

Specifications

| - | |
|---------------------|---|
| Measurement Ranges | Low: 35 to 100dB; High: 65 to 130dB |
| Bandwidth | 31.5Hz to 8kHz |
| Resolution | 0.1dB |
| Accuracy | ±1.5dB |
| Standards | Meets Type 2 ANSI S1.4-1983; IEC 60651, EN60651 |
| Frequency Weighting | A and C (selectable) |
| Response Time | Fast: 125ms / Slow: 1s |
| Power | 9V Battery |
| Dimensions | 9.5.2.7 x 1.9 x 1" (240 x 68 x 25mm) |
| Weight | 6.75oz (210a) |

Ordering Information:

SLM400-KIT Sound Level Meter/Calibrator Kit

SLM400-KIT including Certificate of Traceability to N.I.S.T. SLM400-KIT-NIST











