



PTFE INSULATED EQUIPMENT WIRE TO BS 3G 210 UNSCREENED TYPE B AND NB

Size	Number of Strands	Nominal diameter of strands mm	Nom. diameter of conductor mm	Max Resistance Ω/km @ 20°C		Max Weight Kg/km
				B	NB	
26	1	0.400	0.400	146.0	1.00	2.56
23	1	0.600	0.600	64.3	1.20	4.38
32	7	0.080	0.240	558.0	0.84	1.44
30	7	0.100	0.300	353.0	0.90	1.75
28	7	0.120	0.360	244.0	0.96	2.10
26	7	0.150	0.450	159.0	1.05	2.74
24	7	0.200	0.600	88.30	1.20	3.95
26	19	0.100	0.500	130.0	1.10	3.09
24	19	0.120	0.600	89.8	1.20	3.89
22	19	0.150	0.750	58.6	1.35	5.44
20	19	0.200	1.000	32.5	1.60	8.43
18	19	0.250	1.250	20.6	1.85	12.11

PRODUCT CHARACTERISTICS:

Cable Characteristics

Temperature rating:	Type B - 190°C Type NB - 260°C
Voltage rating:	600 Volts

PTFE INSULATED EQUIPMENT WIRE TO BS 3G 210 UNSCREENED TYPE C AND NC

Size	Number of Strands	Nominal diameter of strands mm	Nom. diameter of conductor mm	Max Resistance Ω/km @ 20°C		Max Weight Kg/km
				C	NC	
19	1	0.900	0.900	28.5	28.6	9.94
32	7	0.080	0.240	558.0	605.0	2.52
30	7	0.100	0.300	353.0	377.0	2.90
28	7	0.120	0.360	244.0	258.0	3.31
26	7	0.150	0.450	159.0	166.0	4.04
24	7	0.200	0.600	88.30	91.2	5.42
26	19	0.100	0.500	130.0	139.0	4.45
24	19	0.120	0.600	89.8	94.9	5.36
22	19	0.150	0.750	58.6	61.3	7.08
20	19	0.200	1.000	32.5	33.6	10.33
18	19	0.250	1.250	20.6	21.2	14.30
16	19	0.300	1.500	14.3	14.6	19.25
14	19	0.335	1.675	11.4	11.6	23.90
12	19	0.450	2.250	6.28	6.38	38.50
10	37	0.400	2.800	4.01	4.08	56.00

PRODUCT CHARACTERISTICS:

Cable Characteristics

Temperature rating:	Type C - 190°C Type NC - 260°C
Voltage rating:	1000 Volts