



Actual

Catalog Number: SPL25/M25/B
Product ID: 7TCA296030R0211
EAN Number: 05020963000355
Status: Active

Nickel Plated Brass Liquid Tight Straight Fitting with Swivel External Thread, Nominal Conduit Size 25 Millimeters, Metric Thread Size M25

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Adaptaflex
Type	Liquid Tight Non-Metallic Fitting
Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Size	3/4 Inch
Material	Brass
Finish	Nickel Plated
Color	Metallic
Connection	Straight
Cable Entry	M25 Thread

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	25mm
Degree of protection (IP) conduit dependant	IP67-IP67
Model	Straight
Revolving thread	Y
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	Metric
Thread connection size	M25 x 1.5
One-piece	Y
Material housing	Brass
Surface protection	Nickel-plated
Thread length	17mm
Total length	57mm
Total height	34mm
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	N
Approved in combination with protective conduit FI	N
Operating temperature	-65-+150°C

Packaging

Outer Quantity	10
Outer Dimensions (inches)	1x1x1
Weight Uom	0.33 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com