

12-Outlet Power Strip with Surge Protection, 15-ft. Cord, 1050 Joules, 36 in. length

MODEL NUMBER: SS3612









Description

The SS3612 power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 12 NEMA 5-15R outlets with 2.48-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in

Highlights

- 12 outlets
- 15-ft. cord
- 36-in. length
- 1050-joule rating

Applications

Offers outlet power distribution
with surge suppression for
multiple loads in equipment
racks, computer rooms,
workbenches and raceways in a
variety of internetworking,
telecommunications, audio/video
and live sound applications.

Package Includes

- SS3612 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 1050 joules. This corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray housing with black output receptacles.

PLUG/OUTLETS: Input: NEMA 5-15P Output: 12 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 3-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 1050 joules

Features

- 3-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more
- · Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 1050 joules
- 12 NEMA 5-15R outlets with 2.48-in. center-to-center spacing
- 15-ft. AC line cord
- Adjustable mounting clips for installation in a wide variety of applications
- Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket
- Rugged all-metal housing
- Lighted power switch with transparent guard to prevent accidental shutoff
- 15A resettable circuit breaker
- Attractive gray housing with black output receptacles



Specifications

Frequency Compatibility 60 Hz Output Receptacles (12) 5- Output (Watts) 1800 Circuit Breaker (amps) 15 Outlet Type NEMA Outlet Spacing 2.48-in USB Charging No 20-Amp Rating No INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
Output (Watts) Circuit Breaker (amps) 15 Outlet Type NEMA Outlet Spacing 2.48-in USB Charging No INPUT Nominal Input Voltage(s) Supported Recommended Electrical Service Input Connection Type Input Cord Length (ft.) Input Cord Length (m) Voltage Compatibility (VAC) Maximum Surge Amps 15 NEMA 15 17 18 18 10 10 10 11 15 16 17 18 18 18 18 18 18 18 18 18	5-15R	
Circuit Breaker (amps) 15 Outlet Type NEMA Outlet Spacing 2.48-in USB Charging No 20-Amp Rating No INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug NEMA		
Outlet Type		
Outlet Spacing 2.48-in USB Charging No 20-Amp Rating No INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
USB Charging No 20-Amp Rating No INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No	n. center-to-center spacing	
INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
INPUT Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
Nominal Input Voltage(s) Supported 120V A Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
Recommended Electrical Service 120V Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No	INPUT	
Input Connection Type NEMA Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No	AC	
Input Cord Length (ft.) 15 Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
Input Cord Length (m) 4.57 Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No	5-15P	
Voltage Compatibility (VAC) 120 Maximum Surge Amps 22000 GFCI Plug No		
Maximum Surge Amps 22000 GFCI Plug No		
GFCI Plug No		
USER INTERFACE, ALERTS & CONTROLS		
	USER INTERFACE, ALERTS & CONTROLS	
Switches Combin	nation AC circuit breaker and lighted 2-position power switch controls power to all outlets	
Locking Switch Cover Transp	parent locking switch cover	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating 1050		
UL1449 Let Through Rating 500V L	JL verified	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection No		
Cable (Coax) Protection No		
Network (Ethernet) Protection No		
PHYSICAL		
Unit Dimensions (hwd / in.) 1.25 x	1.62 x 36	





Unit Dimensions (hwd / cm)	3.18 x 4.11 x 91.44	
Included Mounting Accessories	Set of adjustable mounting clamps	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Color	Gray	
Outlets Measurement (Center to Center)	2.48	
Metal Case	Yes	
SPECIAL FEATURES		
Right-Angle Plug	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide	c) Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies