

(2.54 mm) .100"

SSM SERIES

TIGER CLAW™ SURFACE MOUNT SOCKET

Mates with:

TSW, MTSW, TST, TSS, ZST, ZSS, DW, EW, ZW, TSM, HMTSW, HTSW, TSSH, BST, HTSS, TLW, MTLW

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SSM

Insulator Material: Black Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Au or Sn over 50 μ" (1.27 μm) Ni

Current Rating (SSM/TSW): 5.2 A per pin (2 pins powered)
Voltage Rating: 405 VAC / 572 VDC

Operating Temp Range: -55 °C to +125 °C with Gold
 -55 °C to +105 °C with Tin

Insertion Depth: SV/DV is (4.34 mm) .171" to (7.24 mm) .285" or pass-through from top; (5.56 mm) .219" plus board thickness minimum from bottom; SH/DH is (4.34 mm) .171" to (6.35 mm) .250"

Normal Force: 125 grams (1.21 N) average
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes

-DH Coplanarity: Less than 28 positions (0.15 mm) .006" max*
 More than 27 positions (0.20 mm) .008" max*
-SH, -SV, -DV Coplanarity: (0.15 mm) .006" max*
 *(.004" stencil solution may be available; contact IPG@samtec.com)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality




Note: Some lengths, styles and options are non-standard, non-returnable.

SSM	1	NO. PINS PER ROW	PLATING OPTION	ROW OPTION	OTHER OPTION
02 thru 36 (-SV, -SH, -DH)	TIGER CLAW CONTACT	02 thru 40 (-DV)	-F = Gold flash on contact, Matte Tin on tail	-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail	-BE = Bottom Entry (-DV & -SV only)
			-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail		-S = 30 μ" (0.76 μm) Gold on contact, Matte Tin on tail
					-K = (6.50 mm) .256" DIA Polyimide film Pick & Place Pad (2 positions min.) -DV & -SV only
					-"XXX" = Polarized Position (-BE not available)
					-TR = Tape & Reel Packaging (29 positions max.)

ALSO AVAILABLE (MOQ Required)

- Alignment pin Contact Samtec.

APPLICATIONS



HORIZONTAL

-SV = Single Row Vertical Pin	-DV = Double Row Vertical Pin
-SH = Single Row Horizontal Pin	-DH = Double Row Horizontal Pin

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.