


T350, Tantalum, MnO<sub>2</sub> Tantalum, Commercial Grade, 10  $\mu$ F, 10%, 50 VDC, Radial, Solid Tantalum, Conformal, Dipped, Lead Spacing = 5.08mm

**General Information**

<b>Series:</b>	T350
<b>Dielectric:</b>	MnO <sub>2</sub> Tantalum
<b>Style:</b>	Radial
<b>Description:</b>	Radial, Solid Tantalum, Conformal, Dipped
<b>Features:</b>	Low Leakage
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>AEC-Q200:</b>	No
<b>Notes:</b>	Longest Lead Is Positive.

**Dimensions**

<b>D</b>	8.9mm
<b>H</b>	13.5mm
<b>S</b>	5.08mm +/-0.38mm
<b>LL</b>	12.7mm +/-1.26mm
<b>F</b>	0.5mm +/-0.05mm

**Specifications**

<b>Capacitance:</b>	10 $\mu$ F
<b>Capacitance Tolerance:</b>	10%
<b>Voltage DC:</b>	50 VDC (85C), 33 VDC (125C), 0.5 VDC (125C Reverse)
<b>Temperature Range:</b>	-55/+125°C
<b>Dissipation Factor:</b>	6%
<b>Leakage Current:</b>	4 $\mu$ A

**Packaging Specifications**

<b>Packaging:</b>	Bulk, Bag
<b>Packaging Quantity:</b>	100