


*Sensitive, Low Profile, Hi-Current
Relay Designed to Meet
International Standards*



T75 series

14 Amp, PC Board Miniature Relay

File E29244

File LR45064

File No. 3919

Users should thoroughly review the technical data before selecting a product part number. It is recommended that user also seek out the pertinent approvals files of the agencies/laboratories and review them to ensure the product meets the requirements for a given application.

Features

- High sensitivity – nominal coil power requirement is as low as 212mW.
- Low profile, .591 in. (15mm) tall case uses only .465 in² (3cm²) of area on the printed circuit board, permitting high density circuit design.
- Power switching capability – contacts rated 14 amps in 1 Form A (SPST-NO) or 1 Form C (SPDT) arrangements.
- Designed to meet UL, CSA, VDE, SEMKO and SEV requirements.
- Designed to meet VDE 8mm spacing, 4kV dielectric, coil to contacts.
- Designed to meet 3 mm creepage between contacts.
- Conforms to: VDE 0110 – Insulation Group C (250V)
VDE 435 Part 201 – High current applications
VDE 0804 – Telecommunications equipment
VDE 0631 – Temperature controllers and limiters
VDE 0700 – Household appliances
VDE 0805/5.90 – Office machines
- Immersion cleanable[§], ultrasonically sealed case.
- Well suited for a broad range of applications e.g. HVAC, appliances, security and industrial control.

§ For more details, refer to application note 13C265, "Mounting, Termination and Cleaning of PC Board Relays."

Contact Ratings @ 25°C with relay properly vented. Remove vent nib after soldering and cleaning.

Arrangements: 1 Form A (SPST-NO) and 1 Form C (SPDT).

Material: Silver-cadmium oxide.

Expected Mechanical Life: 20 million operations.

Expected Electrical Life:

- 100,000 operations at 8 amps, 240VAC.
- 50,000 operations at 14 amps NO / 5 amps NC, 120VAC Res.
- 30,000 operations at 7.2 FLA, 45 LRA, 120VAC.
- 10,000 operations at 5 FLA, 30 LRA, 240VAC.
- 30,000 operations at B300 pilot duty (360VA, 240VAC; 470VA, 120VAC).

Contact Ratings (See Figure 1):

Maximum Switched Voltage: 380VAC.
Maximum Switched Current: 14/5 (N.O./N.C.) amps, AC resistive; 8 amps DC (see Fig. 1)


Maximum Switched Power: 200W, DC; 2,000VA, AC.

Minimum Required Contact Load: 12V, 100mA.

VDE Contact Ratings: 8 amps, 250VAC.

UL/CSA Contact Ratings: 10 amps, 240VAC; 8 amps 24VDC; 1/3 HP, 120VAC; 1/2 HP, 240VAC.

Figure 1 - DC Switching Load Limit Curve



Initial Dielectric Strength

Between Open Contacts: 1,000V rms.

Between Contacts and Coil: 4,000V rms, 8mm.

Coil Data

Voltage: 3 to 60VDC.

Maximum Power @ 25°C: 1W.

Nominal Power @ 25°C: 230mW, typ.

Temperature Rise: 85°C per Watt.

Duty Cycle: Continuous.

Coil Data

	Nominal Voltage	DC Resistance in Ohms ±10%	Must Operate Voltage	Nominal Coil Current (mA)
DC Coils	3	40	2.1	75.0
	5	118	3.6	42.4
	6	165	4.3	36.4
	9	365	6.4	24.7
	12	650	8.5	18.5
	18	1,455	12.8	12.4
	24	2,270	17.2	10.6
	36	5,460	25.4	6.4
	48	8,790	34.5	5.5
	60	15,265	42.8	3.9

Operate Data @ 25°C

Must Operate Voltage: 72% of nom. voltage or less.

Must Release Voltage: 10% of nom. voltage or more.

Operate Time (Excluding Bounce): 6 ms, typ., at nom. voltage.

Release Time (Excluding Bounce): 2.5 ms, typ., at nom. voltage.

Maximum Switching Rate: 20 operations/second.

Maximum Continuous Operating Voltage: 225% of nom. voltage.

Temperature Range

Storage: -40°C to +130°C.

Operating: -40°C to +70°C.

Mechanical Data

Termination: Printed circuit terminals.

Enclosures: Immersion cleanable, plastic sealed case.

Weight: 0.65 oz. (18.5g) approximately.

Ordering Information

Typical Part Number ▶

T75 S 5 D 1 1 2 -12

1. Basic Series:
T75 = Low profile, printed circuit board relay.

2. Enclosure:
S = Immersion cleanable, plastic sealed case.

3. Contact Arrangement:
1 = 1 Form A (SPST-NO)
5 = 1 Form C (SPDT)

4. Coil Input:
D = DC voltage

5. Coil Configuration:
1 = Single coil, non-latching (monostable)

6. Mounting and Terminals:
1 = Printed circuit terminals

7. Contact Material:
2 = Silver-cadmium oxide (AgCdO)


8. Coil Voltage:

03 = 3VDC	06 = 6VDC	12 = 12VDC	24 = 24VDC	48 = 48VDC
05 = 5VDC	09 = 9VDC	18 = 18VDC	36 = 36VDC	60 = 60VDC

Our authorized distributors are more likely to maintain the following items in stock for immediate delivery.


- T75S5D112-05
- T75S5D112-12
- T75S5D112-24

Outline Dimensions



CONTACT TERMINALS: .023 x .040 (.58 x 1.02) REF.
COIL TERMINALS: .024 (.61) DIA. REF.


Wiring Diagram (Bottom View)



* ON SINGLE THROW MODELS, ONLY NECESSARY TERMINALS ARE PRESENT.

PC Board Layouts (Bottom Views)

1 Form C



1 Form A

