

TDR500/3-CTV Handheld TDR



- **Simple operation**
- **AUTO set up for instant use**
- **Ultra fast pulse for near end fault identification**
- **Trace HOLD feature**
- **IP54 rating provides durability during real world operation**
- **Designed for use on all CATV cables**

DESCRIPTION

The TDR500/3-CTV is a hand held, compact Time Domain Reflectometer for locating faults on metallic cables. It has a minimum resolution of 0.1 m/0.3 ft and a 5 km/15,000 ft maximum range depending on velocity factor selected and cable type.

Four output impedances are available (25, 50, 75, and 100 Ω) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements

The TDR500/3-CTV has a simple selection option which, together with a 4-way control switch, offers an intuitive operation for the user. The unit is supplied in a soft canvas carrying bag with shoulder strap and rugged snap hook to attach to tool belt, ladder or cable.

APPLICATIONS

The TDR500/3-CTV is primarily designed for service technicians in the CATV industry. It is ideal for testing the physical integrity of cables within a network. The unit is also capable of locating illegal cable taps. Specific cable conditions identified include:

- Bends or crimps in the cable in the cable
- Taps and splits
- Cuts or shorts in the cable
- Water saturations

FEATURES

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. A clear operator controlled cursor allows instant measurement of the distance to the fault.

A trace HOLD feature also allows the operator to freeze a trace on the screen, something not seen on most other handheld TDRs. Extra high resolution together with white-light backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.

- Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 4 in. (10 cm)
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits
- Power blocking filter not required
- Environmental protection to IP54
- 2ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- Display distance in meters or feet
- Uses five AA primary cells

SPECIFICATIONS

Except where otherwise stated, this specification applies at an ambient temperature of 20 °C.

General

Ranges: 10 m, 25 m, 100 m, 250 m, 1000 m, 2500 m, 5000 m (30 ft, 75 ft, 300 ft, 750 ft, 3000 ft, 7500 ft, 15000 ft)

Accuracy: ±1% of range ± pixel at 0.67 VF
[Note- The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.]

Resolution: 1% of range

Input protection: This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV when used with the optional fused test lead set.

Output pulse: 5 volts peak to peak into open circuit. Pulse widths determined by range and cable

Gain: Set for each range with three user selectable steps (in manual operating mode)

Velocity factor: Variable from 0.2 to 0.99 in steps of 0.01

TX null: Automatic

Power down: Automatic after 5 minutes with no key press

Backlight: Stays on for 1 minute with no key press

Batteries: Five (AA) type batteries, Manganese alkali or nickel metal-hydrate cells

Battery life: Up to 14 hours (typical)

Mechanical: The instrument is designed for use indoors or outdoors and is rated to IP54.

Instrument weight: 0.6 kg (1.32 lbs)

Connectors: Two 4 mm-safety terminals

Display: 256 x 128 pixel Graphics LCD

Environmental

Operating temperature: -15 °C to +50 °C (5 °F to 122 °F)

Storage temperature: -20 °C to 70 °C (-4 °F to 158 °F)

Safety: When using the optional fused test lead set this instrument complies with IEC61010-1 for connection to live systems with less than 300 V between the terminals and up to 150 V CAT IV to earth

EMC: Complies with Electromagnetic Compatibility Specifications (Light industrial) BS EN 61326-1, with a minimum performance of 'B' for all immunity tests



ORDERING INFORMATION

Item (Qty)	Cat. No.
TDR500/3-CTV Time Domain Reflectometer	1005-984
Included accessories	
Carry case and strap	2001-322
Instrument rubber boot with built-in stand	6121-636
Socket BNC to 2 x 4 mm 500 Ohm	25965-154
Plug straight BNC adapter	90014-785
Test leads	6231-694
User guide CD	2002-178

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Täby SWEDEN, Ontario
CANADA, Trappes FRANCE, Oberursel
GERMANY, Aargau SWITZERLAND, Dubai
UAE, Mumbai INDIA, Durban SOUTH AFRICA,
Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2008 Cert. no. Q 09250
Registered to ISO 14001:2004 Cert. no. EMS 61597

TDR500-3CTV_DS_US_V01
www.megger.com
Megger is a registered trademark