

- Compact metal case with screw terminal block
- Universal input 88-264 VAC
- Convection cooled (no-fan)
- High efficiency up to 86%
- EMI/EMC compliance with EN 61000-6-3 and EN 61000-6-1
- Compliance to EN 61000-3-2
- Short circuit, overvoltage and overload protection
- IEC/EN/UL 62368-1 safety approvals
- 3 year product warranty



The TXLN series is a family of encased power supplies designed for a wide range of cost critical applications. With a low profile metal case and screw terminal block connection, they are easy to install in any equipment. These power supplies have universal input and comply with European EMC standards and the Low Voltage Directive (LVD).

Models

Order Code	Output Power	Output 1		Output 2		Efficiency
		Vnom	I _{max}	Vnom	I _{max}	
TXLN 035-103	30 W	3.3 VDC	9'000 mA			74 %
TXLN 035-105	35 W	5 VDC	7'000 mA			79 %
TXLN 035-112		12 VDC	3'000 mA			82 %
TXLN 035-115	36 W	15 VDC	2'400 mA			84 %
TXLN 035-124		24 VDC	1'500 mA			85 %
TXLN 035-148	38 W	48 VDC	800 mA			86 %
TXLN 035-212	35 W	+5 VDC	4'000 mA	+12 VDC	2'500 mA	79 %
TXLN 035-215		+5 VDC	4'000 mA	+24 VDC	1'300 mA	79 %
TXLN 035-22M2	36 W	+12 VDC	3'000 mA	-12 VDC	1'500 mA	83 %
TXLN 035-23M3		+15 VDC	2'400 mA	-15 VDC	1'500 mA	84 %

Options

on demand (backorder with MOQ non stocking item)	- Optional model with 7 VDC / 4'700 mA - Optional model with 30 VDC / 1'200 mA
---	---

Note - Total output power must not exceed rated power.

Input Specifications

Input Voltage	- AC Range	88 - 264 VAC (Full Range)
	- DC Range	125 - 375 VDC (Designed for, no certification)
Input Frequency		47 - 63 Hz
Input Current	- Full Load & Vin = 115 VAC	1'000 mA max.
Power Consumption	- At no load	500 mW max. (Ready to meet ErP directive)
Input Inrush Current	- At 230 VAC	50 A max.
	- At 115 VAC	30 A max.
Recommended Input Fuse		(The need of an external fuse has to be assessed in the final application.)

Output Specifications

Output Voltage Adjustment		±10% (single output models only) (By trim potentiometer) Output power must not exceed rated power!		
Voltage Set Accuracy		±3% max. (3.3 Vout model)		
		±2% max. (5 Vout model)		
		±1% max. (other single output models)		
		±2% / ±5% max. (5/12 and 5/24 Vout models)		
		±1% / ±5% max. (other dual output models)		
Regulation	- Input Variation (Vmin - Vmax)	single output models:	1.5% max. (3.3 Vout model)	
			1.0% max. (5 Vout model)	
			0.5% max. (other single output models)	
		dual output models:	0.5% max. (Output 1, 12/-12 and 15/-15 Vout)	
			1.0% max. (Output 1, 5/12 and 5/24 Vout)	
	- Load Variation (0 - 100%)		2.5% max (Output 2)	
		single output models:	3% max. (3.3 Vout model)	
			2% max. (5 Vout model)	
			1% max (other single output models)	
		dual output models:	1% max. (Output 1)	
	5% max. (Output 2)			
		(Output 1 of 5/12 and 5/24 Vout models have 2% max.)		
Ripple and Noise (20 MHz Bandwidth)	- single output	3.3 VDC model:	70 mVp-p max. (w/ 0.1 µF // 47 µF)	
		5 VDC model:	70 mVp-p max. (w/ 0.1 µF // 47 µF)	
		7 VDC model:	80 mVp-p max. (w/ 0.1 µF // 47 µF)	
		12 VDC model:	120 mVp-p max. (w/ 0.1 µF // 47 µF)	
		15 VDC model:	150 mVp-p max. (w/ 0.1 µF // 47 µF)	
		24 VDC model:	150 mVp-p max. (w/ 0.1 µF // 47 µF)	
		30 VDC model:	200 mVp-p max. (w/ 0.1 µF // 47 µF)	
		48 VDC model:	200 mVp-p max. (w/ 0.1 µF // 47 µF)	
		- dual output	5 / 12 VDC model:	70 / 120 mVp-p max. (w/ 0.1 µF // 47 µF)
			5 / 24 VDC model:	70 / 240 mVp-p max. (w/ 0.1 µF // 47 µF)
12 / -12 VDC model:	120 / 120 mVp-p max. (w/ 0.1 µF // 47 µF)			
15 / -15 VDC model:	150 / 150 mVp-p max. (w/ 0.1 µF // 47 µF)			

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

Minimum Load	- single output	3.3 VDC model: 0 % of I _{out} max. 5 VDC model: 0 % of I _{out} max. 7 VDC model: 0 % of I _{out} max. 12 VDC model: 0 % of I _{out} max. 15 VDC model: 0 % of I _{out} max. 24 VDC model: 0 % of I _{out} max. 30 VDC model: 0 % of I _{out} max. 48 VDC model: 0 % of I _{out} max.
	- dual output	5 / 12 VDC model: 7.5 % of I _{out} max. 5 / 24 VDC model: 7.5 % of I _{out} max. 12 / -12 VDC model: 10 % of I _{out} max. 15 / -15 VDC model: 12.5 % of I _{out} max. <small>(dual output models require 300 mA on Output 1)</small>
Temperature Coefficient		±0.02 %/K max.
Hold-up Time	- At 230 VAC	40 ms min.
	- At 115 VAC	20 ms min.
Start-up Time	- At 230 VAC	1'000 ms max.
	- At 115 VAC	1'000 ms max.
Short Circuit Protection		Continuous, Automatic recovery
Output Current Limitation		105 - 150% of I _{out} max.
Overvoltage Protection		115 - 140% of V _{out} nom. <small>(Output 1 only)</small>

Safety Specifications

Safety Standards	- IT / Multimedia Equipment	EN 62368-1 UL 62368-1
	- Certification Documents	www.tracopower.com/overview/txln035
Protection Class		Class I (Prepared): Connection to PE
Pollution Degree		PD 2
Over Voltage Category		OVC II

EMC Specifications

EMI Emissions	- Conducted Emissions	EN 61000-6-3 (Generic Residential) EN 55032 class B (internal filter)
	- Radiated Emissions	EN 55032 class B (internal filter)
	- Harmonic Current Emissions	EN 61000-3-2, class A
	- Voltage Fluctuations & Flicker	EN 61000-3-3
	EMS Immunity	
	- Electrostatic Discharge	Air: EN 61000-4-2, ±8 kV, perf. criteria A Contact: EN 61000-4-2, ±4 kV, perf. criteria A
	- RF Electromagnetic Field	EN 61000-4-3, 3 V/m, perf. criteria A
	- EFT (Burst) / Surge	EN 61000-4-4, ±2 kV, perf. criteria A L to L: EN 61000-4-5, ±1 kV, perf. criteria A L to PE: EN 61000-4-5, ±2 kV, perf. criteria A
	- Conducted RF Disturbances	EN 61000-4-6, 3 V _{rms} , perf. criteria A
	- PF Magnetic Field	Continuous: EN 61000-4-8, 3 A/m, perf. criteria A
	- Voltage Dips & Interruptions	230 VAC / 50 Hz: EN 61000-4-11 30%, 25 periods, perf. criteria A >95%, 0.5 periods, perf. criteria A >95%, 250 periods, perf. criteria C

General Specifications

Relative Humidity		90% max. (non condensing)
Temperature Ranges	- Operating Temperature	-20°C to +70°C
	- Storage Temperature	-40°C to +85°C

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

Power Derating	- High Temperature - Low Input Voltage	2.5 %/K above 50°C 0.83 %/V below 100 VAC
Cooling System		Natural convection (20 LFM)
Altitude During Operation		2'000 m max.
Switching Frequency		65 kHz typ. (PWM)
Insulation System		Reinforced Insulation
Working Voltage (rated)		275 VAC
Isolation Test Voltage	- Input to Output, 60 s - Input to Case or PE, 60 s - Output to Case or PE, 60 s	3'000 VAC 1'500 VAC 500 VAC
Isolation Resistance	- Input to Output, 500 VDC	100 MΩ min.
Leakage Current (at 264 VAC)	- Touch Current	1000 µA max.
Reliability	- Calculated MTBF	400'000 h (single output models) 340'000 h (dual output models)
Housing Material		Aluminium
Connection Type		Screw Terminal
Weight	- single output - dual output	340 g 350 g
Status Indicator		Indicated by green LED
Environmental Compliance	- REACH Declaration - RoHS Declaration	www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant www.tracopower.com/info/rohs-declaration.pdf Exemptions: 6a, 6c, 7a, 7c-I, 7c-II

Supporting Documents


Overview Link (for additional Documents)

www.tracopower.com/overview/txn035

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.


Outline Dimensions

Single Output Models



Screw Terminal	
Pin	Function
1	AC (L)
2	AC (N)
3	FG
4	-Vout
5	+Vout

Dual Output Models



Screw Terminal	
Pin	Function
1	AC (L)
2	AC (N)
3	PE
4	GND
5	Output 1
6	Output 2