



Introducing Raychem Versaflex Expandable, Braided, Polyester Sleeving

Raychem brand Versaflex sleeving is suited for the mechanical protection of wire harnesses and hoses, and all other applications where the highest level of flexibility and abrasion/cut-through resistance is required. Versaflex sleeving serves as an economical means for wire bundling that will not trap heat or moisture, expanding easily to fit over irregular shapes, then contracting to conform to substrates. Versaflex sleeving comes in a flame-retardant (FR) version which meets the UL VW-1 flammability requirement. Versaflex sleeving must be cut with a hot knife to prevent fraying. This product is a cold applied expandable sleeving (non-heat shrink).

Raychem Versaflex Expandable, Braided, Polyester Sleeving



KEY FEATURES

- Expands and contracts easily to fit over a variety of substrates
- Lightweight and flexible
- Flame-retardant (FR) version available
- RoHS Compliant
- This product is cold applied

Tyco Electronics Technical Support Center

USA:	+1 (800) 522-6752
Canada:	+1 (905) 470-4425
Central America & Mexico	+52 (0) 55-1106-0814
South America:	+55 (0) 11-2103-6000
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 8706-080208
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

www.tycoelectronics.com

© 2010 Tyco Electronics Corporation. All Rights Reserved.
7-1773455-2 CIS-PDF-MS 3/2010
Raychem, Versaflex, TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Industries

- Commercial
- Industrial
- Rail
- Maintenance and Repair Organizations (MRO)
- Aerospace and Defense
- Marine

TEMPERATURE RATING:

- Operating Temperature Range : -50°C to 150°C

STANDARDS AND SPECIFICATIONS:

- UL E306976 VW-1, 125°C

ORDERING INFORMATION:

Color	Versaflex: Black (-0) Versaflex FR: Black with white X tracer (-09)
Standard Packaging	On spools
Ordering Description	Specify product name, size and color (Example: VERSAFLEX FR-1/4-09-SP)

PRODUCT DIMENSIONS:

Versaflex		Versaflex FR (Flame-Retardant)	
Size (in.)	Size Range mm [in]	Size (in.)	Size Range mm [in]
1/8	2.4-6.4 [0.094-0.252]	1/8	2.4-6.4 [0.094-0.252]
1/4	3.2-9.5 [0.125-0.375]	1/4	3.2-9.5 [0.125-0.375]
3/8	4.7-16 [0.185-0.630]	3/8	4.7-16 [0.185-0.630]
1/2	6.4-19 [0.252-0.748]	1/2	6.4-19 [0.252-0.748]
3/4	13-32 [0.512-1.260]	3/4	13-32 [0.512-1.260]
1-1/4	19-45 [0.748-1.772]	1-1/4	19-45 [0.748-1.772]
1-3/4	32-70 [1.260-2.756]	1-3/4	32-70 [1.260-2.756]
2	38-76 [1.496-2.992]	2	38-76 [1.496-2.992]



Our commitment. Your advantage.

While Tyco Electronics has made every reasonable effort to ensure the accuracy of the information in this catalog, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult Tyco Electronics for the latest dimensions and design specifications.