



Home > Products > Wirewound Resistors > VP Fixed > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

VP25K5000



Actual product appearance may vary.

VP Fixed Series, 5 kOhms, 25.0 W, Fixed, Wirewound Resistor

Features

Rugged vitreous enamel coating
Suitable for high wattage applications
All-welded construction
Meets or exceeds MIL-R-26 standards

Potential Applications

Power supplies
Power dissipation circuits
Load adjusters for power amplifiers

Description

The VP and VK Series resistors are intended for applications requiring high power resistors. The resistors have lug terminals, which are solderable and they can also be bracket mounted. They have tinned lug terminals solderable to MIL-R-26 standards. They have tubular ceramic cores and vitreous enamel coatings and are very suitable for rugged applications. These resistors can be bracket mounted.

Note: Not suitable for high frequency applications.

Supporting Documentation

[▶ Dimensions](#)

[▶ Mounting Bracket](#)

Product Specifications	
Resistor Type	Fixed
Power Rating	25 W
Resistance Value	5 KOhms
Terminal Type	Lug
Housing Material	Vitreous enamel
Tolerance	± 5%
Temperature Coefficient	± 100 ppm/ °C
Availability	Global
UNSPSC Code	32121608
UNSPSC Commodity	32121608 Wire Wound Resistor
Series Name	VP Fixed

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)