



Fast Recovery Diodes (Stud Version), 6/12/16 A



DO-203AA (DO-4)

FEATURES

- Short reverse recovery time
- Low stored charge
- Wide current range
- Excellent surge capabilities
- Standard JEDEC types
- Stud cathode and stud anode versions
- Fully characterized reverse recovery conditions
- RoHS compliant



RoHS
COMPLIANT

TYPICAL APPLICATIONS

- DC power supplies
- Inverters
- Converters
- Choppers
- Ultrasonic systems
- Freewheeling diodes

PRODUCT SUMMARY

$I_{F(AV)}$	6/12/16 A
-------------	-----------

MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	1N3879. TO 1N3883.	1N3889. TO 1N3893.	6FL..	12FL..	16FL..	UNITS
$I_{F(AV)}$	$T_C = 100\text{ }^\circ\text{C}$	6 ⁽¹⁾	12 ⁽¹⁾	6	12	16	A
$I_{F(RMS)}$		9.5	19	9.5	19	25	A
I_{FSM}	50 Hz	72	145	110	145	180	A
	60 Hz	75 ⁽¹⁾	150 ⁽¹⁾	115	150	190	
I^2t	50 Hz	26	103	60	103	160	A ² s
	60 Hz	23	94	55	94	150	
$I^2\sqrt{t}$		363	856	1452	1452	2290	$I^2\sqrt{s}$
V_{RRM}	Range	50 to 400 ⁽¹⁾		50 to 1000			V
t_{rr}		See Recovery Characteristics table					ns
T_J	Range	- 65 to 150					$^\circ\text{C}$

Note

⁽¹⁾ JEDEC registered values

1N3879(R), 1N3889(R), 6/12/16FL(R) Series



Vishay High Power Products Fast Recovery Diodes
(Stud Version), 6/12/16 A

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS						
TYPE NUMBER	VOLTAGE CODE	V _{RRM} , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE V	V _{RSM} , MAXIMUM NON-REPETITIVE PEAK VOLTAGE V	I _{RRM} MAXIMUM AT T _J = 25 °C μA	I _{RRM} MAXIMUM AT T _J = 100 °C mA	I _{RRM} MAXIMUM AT T _J = 150 °C mA
1N3879.	-	50	75	15 ⁽¹⁾	1.0 ⁽¹⁾	3.0 ⁽¹⁾
1N3880.		100	150			
1N3881.		200	250			
1N3882.		300	350			
1N3883.		400	450			
1N3889.	-	50	75	25 ⁽¹⁾	3.0 ⁽¹⁾	5.0 ⁽¹⁾
1N3890.		100	150			
1N3891.		200	250			
1N3892.		300	350			
1N3893.		400	450			
6FL..	5	50	75	50	-	6.0
12FL..	10	100	150			
16FL..	20	200	275			
	40	400	500			
	60	600	725			
	80	800	950			
	100	1000	1250			

Note

(1) JEDEC registered values

FORWARD CONDUCTION									
PARAMETER	SYMBOL	TEST CONDITIONS			1N3879. 1N3883.	6FL..	1N3889. 1N3893. 12FL..	16FL..	UNITS
Maximum average forward current at case temperature	I _{F(AV)}	180° conduction, half sine wave DC			6 ⁽¹⁾	6	12 ⁽¹⁾	16	A
					100	100	100	100	°C
Maximum RMS current	I _{F(RMS)}				9.5	9.5	19	25	A
Maximum peak, one-cycle non-repetitive forward current	I _{FSM}	t = 10 ms	No voltage reappplied	Sinusoidal half wave, initial T _J = 150 °C	85	130	170	215	
		t = 8.3 ms			90	135	180	225	
		t = 10 ms	100 % V _{RRM} reappplied		72	110	145	180	
		t = 8.3 ms			75 ⁽¹⁾	115	150 ⁽¹⁾	190	
Maximum I ² t for fusing	I ² t	t = 10 ms	No voltage reappplied		36	86	145	230	A ² s
		t = 8.3 ms			33	78	130	210	
		t = 10 ms	100 % V _{RRM} reappplied		26	60	103	160	
		t = 8.3 ms			23	55	94	150	
Maximum I ² √t for fusing	I ² √t	t = 0.1 to 10 ms, no voltage reappplied			363	856	1452	2290	A ² √s
Maximum forward voltage drop	V _{FM}	T _J = 25 °C; I _F = Rated I _{F(AV)} (DC)			1.4 ⁽¹⁾	1.4	1.4 ⁽¹⁾	1.4	V
		T _C = 100 °C; I _{FM} = π x rated I _{F(AV)}			1.5 ⁽¹⁾	1.5	1.5 ⁽¹⁾	1.5	V

Note


(1) JEDEC registered values



1N3879(R), 1N3889(R), 6/12/16FL(R) Series

Fast Recovery Diodes Vishay High Power Products
(Stud Version), 6/12/16 A

RECOVERY CHARACTERISTICS							
PARAMETER	SYMBOL	TEST CONDITIONS	1N3879. 1N3883.	1N3889. 1N3893.	6FL.. 12FL.. 16FL..		UNITS
					S02	S05	
Maximum reverse recovery time	t_{rr}	$T_J = 25\text{ }^\circ\text{C}$, $I_F = 1\text{ A}$ to $V_R = 30\text{ V}$, $di_F/dt = 100\text{ A}/\mu\text{s}$	150	150	-	-	ns
		$T_J = 25\text{ }^\circ\text{C}$, $di_F/dt = 25\text{ A}/\mu\text{s}$, $I_{FM} = \pi \times \text{rated } I_{F(AV)}$	300 (1)	300 (1)	200	500	
Maximum peak recovery current	$I_{RM(REC)}$	$I_{FM} = \pi \times \text{rated } I_{F(AV)}$	4 (1)	5 (1)	-		-
Maximum reverse recovery charge	Q_{rr}	$T_J = 25\text{ }^\circ\text{C}$, $I_F = 1\text{ A}$ to $V_R = 30\text{ V}$, $di_F/dt = 100\text{ A}/\mu\text{s}$	400	350	-	-	nC
		$T_J = 25\text{ }^\circ\text{C}$, $di_F/dt = 25\text{ A}/\mu\text{s}$, $I_{FM} = \pi \times \text{rated } I_{F(AV)}$	400	400	-	-	



Note

(1) JEDEC registered values

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS	1N3879. 1N3883. 6FL..	1N3889. 1N3893. 12FL..	16FL..	UNITS
Maximum junction operating temperature range	T_J		- 65 to 150			$^\circ\text{C}$
Maximum storage temperature range	T_{Stg}		- 65 to 175			
Maximum thermal resistance, junction to case	R_{thJC}	DC operation	2.5	2.0	1.6	$^\circ\text{C}/\text{W}$
Maximum thermal resistance, case to heatsink	R_{thCS}	Mounting surface, smooth, flat and greased	0.5			
Allowable mounting torque		Not lubricated threads	1.5 + 0 - 10 % (13)			N · m (lbf · in)
		Lubricated threads	1.2 + 0 - 10 % (10)			
Approximate weight			7			g
			0.25			oz.
Case style		JEDEC	DO-203AA (DO-4)			

1N3879(R), 1N3889(R), 6/12/16FL(R) Series



Vishay High Power Products Fast Recovery Diodes
(Stud Version), 6/12/16 A

ΔR_{thJC} CONDUCTION								
CONDUCTION ANGLE	1N3879. 1N3883. 6FL..	1N3889. 1N3893. 12FL..	16FL..	1N3879. 1N3883. 6FL..	1N3889. 1N3893. 12FL..	16FL..	TEST CONDITIONS	UNITS
	SINUSOIDAL CONDUCTION			RECTANGULAR CONDUCTION				
180°	0.58	0.46	0.37	0.33	0.26	0.21	$T_J = 150\text{ }^\circ\text{C}$	K/W
120°	0.60	0.48	0.39	0.58	0.46	0.37		
60°	1.28	1.02	0.82	1.28	1.02	0.82		
30°	2.20	1.76	1.41	2.20	1.76	1.41		

Note

- The table above shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Average Forward Current vs. Maximum Allowable Case Temperature, 1N3879 and 6FL Series




Fig. 3 - Average Forward Current vs. Maximum Allowable Case Temperature, 16FL Series




Fig. 2 - Average Forward Current vs. Maximum Allowable Case Temperature, 1N3889 and 12FL Series




Fig. 4 - Reverse Recovery Time Test Waveform



1N3879(R), 1N3889(R), 6/12/16FL(R) Series

Fast Recovery Diodes Vishay High Power Products
(Stud Version), 6/12/16 A




Fig. 5 - Current Rating Nomogram (Sinusoidal Waveforms), 1N3879 and 6FL Series




Fig. 6 - Current Rating Nomogram (Rectangular Waveforms), 1N3879 and 6FL Series




Fig. 7 - Current Rating Nomogram (Sinusoidal Waveforms), 1N3889 and 12FL Series

1N3879(R), 1N3889(R), 6/12/16FL(R) Series

Vishay High Power Products Fast Recovery Diodes
(Stud Version), 6/12/16 A




Fig. 8 - Current Rating Nomogram (Rectangular Waveforms), 1N3889 and 12FL Series




Fig. 9 - Current Rating Nomogram (Sinusoidal Waveforms), 16FL Series




Fig. 10 - Current Rating Nomogram (Rectangular Waveforms), 16FL Series



1N3879(R), 1N3889(R), 6/12/16FL(R) Series

Fast Recovery Diodes
(Stud Version), 6/12/16 A

Vishay High Power Products




Fig. 11 - Maximum Forward Voltage vs. Forward Current, 1N3879 and 6FL Series




Fig. 14 - Maximum High Level Forward Power Loss vs. Average Forward Current, 1N3889 and 12FL Series




Fig. 12 - Maximum High Level Forward Power Loss vs. Average Forward Current, 1N3879 and 6FL Series




Fig. 15 - Maximum Forward Voltage vs. Forward Current, 16FL Series




Fig. 13 - Maximum Forward Voltage vs. Forward Current, 1N3889 and 12FL Series




Fig. 16 - Maximum High Level Forward Power Loss vs. Average Forward Current, 16FL Series

1N3879(R), 1N3889(R), 6/12/16FL(R) Series



Vishay High Power Products Fast Recovery Diodes
(Stud Version), 6/12/16 A




Fig. 17a - Typical Reverse Recovery Time vs. Rate of Fall of Forward Current, All Series ...S02




Fig. 18b - Typical Recovered Charge vs. Rate of Fall of Forward Current, All Series ...S05




Fig. 17b - Typical Recovered Charge vs. Rate of Fall of Forward Current, All Series ...S02




Fig. 19a - Typical Reverse Recovery Time vs. Rate of Fall of Forward Current, All Series ...S10




Fig. 18a - Typical Reverse Recovery Time vs. Rate of Fall of Forward Current, All Series ...S05




Fig. 19b - Typical Recovered Charge vs. Rate of Fall of Forward Current, All Series ...S10



1N3879(R), 1N3889(R), 6/12/16FL(R) Series

Fast Recovery Diodes Vishay High Power Products
(Stud Version), 6/12/16 A




Fig. 20 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 1N3879 Series




Fig. 22 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 1N3889 and 12FL Series




Fig. 21 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 6FL Series




Fig. 23 - Maximum Non-Repetitive Surge Current vs. Number of Current Pulses, 16FL Series




Fig. 24 - Maximum Transient Thermal Impedance, Junction to Case vs. Pulse Duration, All Series

1N3879(R), 1N3889(R), 6/12/16FL(R) Series



Vishay High Power Products Fast Recovery Diodes
(Stud Version), 6/12/16 A

ORDERING INFORMATION TABLE

Device code	16	F	L	R	60	M	S02
	①	②	③	④	⑤	⑥	⑦


- 1** - Current code $I_{(AVG)}$ = Exact current rating
- 2** - F = Diode
- 3** - Omit = Standard recovery diode
L = Only for fast diode
- 4** - Omit = Stud forward polarity
R = Stud reverse polarity
- 5** - Voltage code x 10 = V_{RRM} (see Voltage Ratings table)
- 6** - Outlines:
Omit = Stud base UNF thread
M = Stud base metric thread
- 7** - t_{rr} code only for fast diode (see Recovery Characteristics table)

LINKS TO RELATED DOCUMENTS

Dimensions	http://www.vishay.com/doc?95311
------------	---

DO-203AB (DO-5) for 40HFL, 70HFL and 85HFL

DIMENSIONS FOR 40HFL/70HFL in millimeters (inches)




Outline Dimensions

Vishay Semiconductors

DO-203AB (DO-5) for
40HFL, 70HFL and 85HFL



DIMENSIONS FOR 85HFL in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.